

Nonmetallic Sheathed and Service Entrance Cable Connectors

Nonmetallic Sheathed Cable * Connector With Cam Lock

Applications

- To ground and secure nonmetallic sheathed cable to boxes and enclosures.

Features


- Positive-stop locking action.
- Used with 14-2, 12-2 and 10-2 (with or without ground).

Standard Material

- Thermoplastic

Certifications and Compliances

- UL Standard: 514B
- UL Listed: E23237
- NEMA: FB-1



Catalog Number	Trade Size (Inches)	Dimensions in Inches/Millimeters			Weight Lbs./Kgs. Per 100
		A	B	C	
A-1 †	1/2	1.09/27.7	0.13/3.3	1.00/25.4	1.30/0.59

Nonmetallic Sheathed Cable and Service Entrance Cable * Connectors

Applications

- To ground and secure nonmetallic sheathed and service entrance cable to boxes and enclosures.

Features


- Furnished with locknut.
- Male hub threads — NPS.

Standard Material/Finish


- Malleable iron

Certifications and Compliances

- UL Standard: 514B
- UL Listed: E23237
- CSA Standard: C22.2 No. 18.3
- CSA Certified: 065178
- NEMA: FB-1



15233



15237

Catalog Number	Trade Size (Inches)	Cable Opening (In./Mm)		Dimensions in Inches/Millimeters			Weight Lbs./Kgs. Per 100
		Max.	Min.	A	B	C	
15233	3/4	0.74/18.8	0.44/11.2	0.66/16.8	0.44/11.2	1.81/46.0	14.40/6.53
15234	1	0.97/24.6	0.50/12.7	0.66/16.8	0.56/14.2	2.03/51.6	21.00/9.53
15235	1-1/4	1.31/33.3	0.81/20.6	0.66/16.8	0.56/14.2	2.38/60.5	30.10/13.65
15236	1-1/2	1.59/40.4	0.81/20.6	0.81/20.6	0.75/19.1	2.63/66.8	53.00/24.04
15237	2	2.00/50.8	1.00/25.4	0.94/23.9	0.75/19.1	3.25/82.6	80.00/36.29

* Select connectors by physical dimensions of cable as dimensions may vary between manufacturers.

† Not CSA certified