


Table No. 1 **Steel Single Sprockets with Browning Split Taper® Bushings**

Part No.	Bushing	Bore Range	DIAMETERS		No. Teeth	Type	DIMENSIONS						Wt. Less Bushing
			Outside	Pitch			T Nom.	OL	L	P	C	H	
<b>SMALLER SIZES ON PRECEDING PAGE</b>													
40P34	P1	1/2-1 3/4"	5.70"	5.419"	34	4	.284"	2 3/16"	1 15/16"	1 21/32"	0	3"	2.8
40P35	P1	1/2-1 3/4	5.86	5.578	35	4	.284	2 3/16	1 15/16	1 21/32	0	3	2.9
40P36	P1	1/2-1 3/4	6.02	5.737	36	4	.284	2 3/16	1 15/16	1 21/32	0	3	3.1
40P37	P1	1/2-1 3/4	6.18	5.896	37	4	.284	2 3/16	1 15/16	1 21/32	0	3	3.3
40P38	P1	1/2-1 3/4	6.33	6.055	38	4	.284	2 3/16	1 15/16	1 21/32	0	3	3.3
40P40	P1	1/2-1 3/4	6.65	6.373	40	4	.284	2 3/16	1 15/16	1 21/32	0	3	3.5
40P41	P1	1/2-1 3/4	6.81	6.532	41	4	.284	2 3/16	1 15/16	1 21/32	0	3	3.6
40P42	P1	1/2-1 3/4	6.97	6.691	42	4	.284	2 3/16	1 15/16	1 21/32	0	3	3.9
40P44	P1	1/2-1 3/4	7.29	7.009	44	4	.284	2 3/16	1 15/16	1 21/32	0	3	4.0
40P45	P1	1/2-1 3/4	7.45	7.168	45	4	.284	2 3/16	1 15/16	1 21/32	0	3	4.2
40P47	P1	1/2-1 3/4	7.77	7.486	47	4	.284	2 3/16	1 15/16	1 21/32	0	3	4.6
40P48	P1	1/2-1 3/4	7.93	7.645	48	4	.284	2 3/16	1 15/16	1 21/32	0	3	4.8
40P50	P1	1/2-1 3/4	8.25	7.963	50	4	.284	2 3/16	1 15/16	1 21/32	0	3	5.0
40P54	P1	1/2-1 3/4	8.89	8.599	54	4	.284	2 3/16	1 15/16	1 21/32	0	3	5.5
40P56	P1	1/2-1 3/4	9.20	8.917	56	4	.284	2 3/16	1 15/16	1 21/32	0	3	5.9
40P60	P1	1/2-1 3/4	9.84	9.554	60	4	.284	2 3/16	1 15/16	1 21/32	0	3	6.6
40Q60	Q1	3/4-2 11/16	9.84	9.554	60	4	.284	2 25/32	2 1/2	2 7/32	0	4 1/8	8.8
40P70	P1	1/2-1 3/4	11.43	11.145	70	4	.284	2 3/16	1 15/16	1 21/32	0	3	8.6
40Q70	Q1	3/4-2 11/16	11.43	11.145	70	4	.284	2 25/32	2 1/2	2 7/32	0	4 1/8	11.0
40Q72	Q1	3/4-2 11/16	11.75	11.463	72	4	.284	2 25/32	2 1/2	2 7/32	0	4 1/8	11.2
40Q80	Q1	3/4-2 11/16	13.03	12.736	80	4	.284	2 25/32	2 1/2	2 7/32	0	4 1/8	13.1
40Q84	Q1	3/4-2 11/16	13.66	13.372	84	4	.284	2 25/32	2 1/2	2 7/32	0	4 1/8	14.1
40Q96	Q1	3/4-2 11/16	15.57	15.281	96	4	.284	2 25/32	2 1/2	2 7/32	0	4 1/8	17.3
40Q112	Q1	3/4-2 11/16	18.12	17.828	112	4	.284	2 25/32	2 1/2	2 7/32	0	4 1/8	12.8




Where two sprockets with the same number of teeth but different bushings are offered, we suggest using the sprocket bushing for heavier service drives.

Table No. 2 **Steel Single Sprockets with Q-D® Bushings**

Part No.	Bushing	Bore Range	DIAMETERS		No. Teeth	Type	DIMENSIONS					Wt. Less Bushing
			Outside	Pitch			T Norm.	OL	L	P	H	
H40JA15*	JA	1/2 - 1 1/4	2.65	2.405	15	QD-1	.284"	1 5/16"	1	7/8	2	.34
H40JA16	JA	1/2 - 1 1/4	2.81	2.563	16	QD-1	.284	1 5/16	1	7/8	2	.43
H40JA17	JA	1/2 - 1 1/4	2.98	2.721	17	QD-1	.284	1 5/16	1	7/8	2	.53
H40JA18	JA	1/2 - 1 1/4	3.14	2.879	18	QD-1	.284	1 5/16	1	7/8	2	.58
H40JA19	JA	1/2 - 1 1/4	3.30	3.038	19	QD-1	.284	1 5/16	1	7/8	2	.64
H40SH20*	SH	1/2 - 1 5/8	3.46	3.196	20	QD-1	.284	1 23/32	1 5/16	1 7/32	2 11/16	.86
H40SH21	SH	1/2 - 1 5/8	3.62	3.355	21	QD-1	.284	1 23/32	1 5/16	1 7/32	2 11/16	1.07
H40SH22	SH	1/2 - 1 5/8	3.78	3.513	22	QD-1	.284	1 23/32	1 5/16	1 7/32	2 11/16	1.17
H40SH23	SH	1/2 - 1 5/8	3.94	3.672	23	QD-1	.284	1 23/32	1 5/16	1 7/32	2 11/16	1.27
H40SH24	SH	1/2 - 1 5/8	4.10	3.831	24	QD-1	.284	1 23/32	1 5/16	1 7/32	2 11/16	1.35
H40SH25	SH	1/2 - 1 5/8	4.26	3.989	25	QD-1	.284	1 23/32	1 5/16	1 7/32	2 11/16	1.42
H40SH26	SH	1/2 - 1 5/8	4.42	4.148	26	QD-1	.284	1 23/32	1 5/16	1 7/32	2 11/16	1.50
H40SH27	SH	1/2 - 1 5/8	4.58	4.307	27	QD-1	.284	1 23/32	1 5/16	1 7/32	2 11/16	1.57
H40SH28	SH	1/2 - 1 5/8	4.74	4.466	28	QD-1	.284	1 23/32	1 5/16	1 7/32	2 11/16	1.65
H40SH30	SH	1/2 - 1 5/8	5.06	4.783	30	QD-1	.284	1 23/32	1 5/16	1 7/32	2 11/16	1.82
40SH32	SH	1/2 - 1 5/8	5.38	5.101	32	QD-1	.284	1 23/32	1 5/16	1 7/32	2 11/16	1.99
40SH35	SH	1/2 - 1 5/8	5.86	5.578	35	QD-1	.284	1 23/32	1 5/16	1 7/32	2 11/16	2.27
40SDS36	SDS	1/2 - 2	6.02	5.737	36	QD-1	.284	1 21/32	1 13/16	1 5/32	3 1/8	2.26
40SDS40	SDS	1/2 - 2	6.65	6.373	40	QD-1	.284	1 21/32	1 13/16	1 5/32	3 1/8	2.69
40SDS42	SDS	1/2 - 2	6.97	6.691	42	QD-1	.284	1 21/32	1 13/16	1 5/32	3 1/8	2.92
40SDS45	SDS	1/2 - 2	7.45	7.168	45	QD-1	.284	1 21/32	1 13/16	1 5/32	3 1/8	3.29
40SDS48	SDS	1/2 - 2	7.93	7.645	48	QD-1	.284	1 21/32	1 13/16	1 5/32	3 1/8	3.68
40SDS54	SDS	1/2 - 2	8.89	8.599	54	QD-1	.284	1 21/32	1 13/16	1 5/32	3 1/8	4.54
40SDS60	SDS	1/2 - 2	9.84	9.554	60	QD-1	.284	1 21/32	1 13/16	1 5/32	3 1/8	5.5
40SK70	SK	1/2 - 2 5/8	11.43	11.145	70	QD-1	.284	2 11/32	1 15/16	1 25/32	3 7/8	8.3
40SK72	SK	1/2 - 2 5/8	11.75	11.463	72	QD-1	.284	2 11/32	1 15/16	1 25/32	3 7/8	8.7
40SK80	SK	1/2 - 2 5/8	13.03	12.736	80	QD-1	.284	2 11/32	1 15/16	1 25/32	3 7/8	10.4
40SK84	SK	1/2 - 2 5/8	13.66	13.372	84	QD-1	.284	2 11/32	1 15/16	1 25/32	3 7/8	11.4
40SK96	SK	1/2 - 2 5/8	15.57	15.281	96	QD-1	.284	2 11/32	1 15/16	1 25/32	3 7/8	14.4
40SK112	SK	1/2 - 2 5/8	18.12	17.828	112	QD-1	.284	2 11/32	1 15/16	1 25/32	3 7/8	19.1

\* Bushings mounts with capscrews on "A" side only



↑ HARDENED TEETH ↓