



Table No. 1 **Steel Single Sprockets with Browning Split Taper® Bushings**



↑ HARDENED TEETH ↓



Part No.	Bushing	Bore Range	DIAMETERS		No. Teeth	Type	DIMENSIONS						Wt. Less Bushing
			Outside	Pitch			T Nom.	OL	L	P	C	H	
H50Q26	Q1	3/4 - 2 11/16	5.52	5.185	26	4	0.343	2 25/32	2 1/2	2 5/32	0	4 1/8	3.8
H50H27	H	3/8 - 1 1/2	5.72	5.384	27	3	0.343	1 1/2	1 1/4	31/32	1/16	2 1/2	2.2
H50P27	P1	1/2 - 1 3/4	5.72	5.384	27	4	0.343	2 3/16	2 15/16	1 19/32	0	3	3.0
H50Q27	Q1	3/4 - 2 11/16	5.72	5.384	27	4	0.343	2 25/32	2 1/2	2 5/32	0	4 1/8	3.9
H50H28	H	3/8 - 1 1/2	5.92	5.582	28	3	0.343	1 1/2	1 1/4	31/32	1/16	2 1/2	2.5
H50P28	P1	1/2 - 1 3/4	5.92	5.582	28	4	0.343	2 3/16	2 15/16	1 19/32	0	3	3.2
H50Q28	Q1	3/4 - 2 11/16	5.92	5.582	28	4	0.343	2 25/32	2 1/2	2 5/32	0	4 1/8	4.0
H50P29	P1	1/2 - 1 3/4	6.12	5.781	29	4	0.343	2 3/16	2 15/16	1 19/32	0	3	3.3
H50H30	H	3/8 - 1 1/2	6.32	5.979	30	3	0.343	1 1/2	1 1/4	31/32	1/16	2 1/2	2.9
H50P30	P1	1/2 - 1 3/4	6.32	5.979	30	4	0.343	2 3/16	2 15/16	1 19/32	0	3	3.5
H50Q30	Q1	3/4 - 2 11/16	6.32	5.979	30	4	0.343	2 25/32	2 1/2	2 5/32	0	4 1/8	5.6
H50H32	H	3/8 - 1 1/2	6.72	6.376	32	3	0.343	1 1/2	1 1/4	31/32	1/16	2 1/2	3.2
H50H33	H	3/8 - 1 1/2	6.92	6.575	33	3	0.343	1 1/2	1 1/4	31/32	1/16	2 1/2	3.4
H50H34	H	3/8 - 1 1/2	7.12	6.774	34	3	0.343	1 1/2	1 1/4	31/32	1/16	2 1/2	3.7
H50H35	H	3/8 - 1 1/2	7.32	6.972	35	3	0.343	1 1/2	1 1/4	31/32	1/16	2 1/2	3.8
H50H36	H	3/8 - 1 1/2	7.52	7.171	36	3	0.343	1 1/2	1 1/4	31/32	1/16	2 1/2	4.0
H50H38	H	3/8 - 1 1/2	7.92	7.569	38	3	0.343	1 1/2	1 1/4	31/32	1/16	2 1/2	4.4
H50H40	H	3/8 - 1 1/2	8.32	7.996	40	3	0.343	1 1/2	1 1/4	31/32	1/16	2 1/2	4.8
50P31	P1	1/2 - 1 3/4	6.52	6.178	31	4	0.343	2 3/16	2 15/16	1 19/32	0	3	3.6
50P32	P1	1/2 - 1 3/4	6.72	6.376	32	4	0.343	2 3/16	2 15/16	1 19/32	0	3	3.9
50Q32	Q1	3/4 - 2 11/16	6.72	6.376	32	4	0.343	2 25/32	2 1/2	2 5/32	0	4 1/8	6.1
50P33	P1	1/2 - 1 3/4	6.92	6.575	33	4	0.343	2 3/16	2 15/16	1 19/32	0	3	4.1
50P34	P1	1/2 - 1 3/4	7.12	6.774	34	4	0.343	2 3/16	2 15/16	1 19/32	0	3	4.3
50P35	P1	1/2 - 1 3/4	7.32	6.972	35	4	0.343	2 3/16	2 15/16	1 19/32	0	3	4.3
50Q35	Q1	3/4 - 2 11/16	7.32	6.972	35	4	0.343	2 25/32	2 1/2	2 5/32	0	4 1/8	6.8
50P36	P1	1/2 - 1 3/4	7.52	7.171	36	4	0.343	2 3/16	2 15/16	1 19/32	0	3	4.8
50Q36	Q1	3/4 - 2 11/16	7.52	7.171	36	4	0.343	2 25/32	2 1/2	2 5/32	0	4 1/8	6.8
50Q37	Q1	3/4 - 2 11/16	7.72	7.370	37	4	0.343	2 25/32	2 1/2	2 5/32	0	4 1/8	7.0
50Q38	Q1	3/4 - 2 11/16	7.92	7.569	38	4	0.343	2 25/32	2 1/2	2 5/32	0	4 1/8	7.4
50Q39	Q1	3/4 - 2 11/16	8.12	7.767	39	4	0.343	2 25/32	2 1/2	2 5/32	0	4 1/8	7.6
50Q40	Q1	3/4 - 2 11/16	8.32	7.966	40	4	0.343	2 25/32	2 1/2	2 5/32	0	4 1/8	8.0
50Q41	Q1	3/4 - 2 11/16	8.52	8.165	41	4	0.343	2 25/32	2 1/2	2 5/32	0	4 1/8	8.2
50Q42	Q1	3/4 - 2 11/16	8.72	8.363	42	4	0.343	2 25/32	2 1/2	2 5/32	0	4 1/8	8.3
50Q44	Q1	3/4 - 2 11/16	9.11	8.761	44	4	0.343	2 25/32	2 1/2	2 5/32	0	4 1/8	8.6
50Q45	Q1	3/4 - 2 11/16	9.31	8.960	45	4	0.343	2 25/32	2 1/2	2 5/32	0	4 1/8	9.0
50Q47	Q1	3/4 - 2 11/16	9.71	9.357	47	4	0.343	2 25/32	2 1/2	2 5/32	0	4 1/8	9.3
50Q48	Q1	3/4 - 2 11/16	9.91	9.556	48	4	0.343	2 25/32	2 1/2	2 5/32	0	4 1/8	9.6
50Q50	Q1	3/4 - 2 11/16	10.31	9.954	50	4	0.343	2 25/32	2 1/2	2 5/32	0	4 1/8	9.8
50Q54	Q1	3/4 - 2 11/16	11.11	10.749	54	4	0.343	2 25/32	2 1/2	2 5/32	0	4 1/8	11.3
50Q56	Q1	3/4 - 2 11/16	11.50	11.147	56	4	0.343	2 25/32	2 1/2	2 5/32	0	4 1/8	12.3
50Q60	Q1	3/4 - 2 11/16	12.30	11.942	60	4	0.343	2 25/32	2 1/2	2 5/32	0	4 1/8	13.3
50Q70	Q1	3/4 - 2 11/16	14.29	13.931	70	4	0.343	2 25/32	2 1/2	2 5/32	0	4 1/8	16.9
50Q72	Q1	3/4 - 2 11/16	14.69	14.329	72	4	0.343	2 25/32	2 1/2	2 5/32	0	4 1/8	18.1
50Q80	Q1	3/4 - 2 11/16	16.28	15.92	80	4	0.343	2 25/32	2 1/2	2 5/32	0	4 1/8	21.1
50Q84	Q1	3/4 - 2 11/16	17.08	16.715	84	4	0.343	2 25/32	2 1/2	2 5/32	0	4 1/8	24.3
50Q96	Q1	3/4 - 2 11/16	19.47	19.102	96	4	0.343	2 25/32	2 1/2	2 5/32	0	4 1/8	29.8
50Q112	Q1	3/4 - 2 11/16	22.65	22.285	112	4	0.343	2 25/32	2 1/2	2 5/32	0	4 1/8	39.3

Where two sprockets with the same number of teeth but different bushings are offered, we suggest using the sprocket bushing for heavier service drives.