


Table No. 1

Steel Finished Bore Single Sprockets


Part No.	DIAMETERS		No. Teeth	Type	STOCK BORES MARKED "X"												DIMENSIONS			Wt. Lbs.
	Outside	Pitch			3/4"	7/8"	1"	1 1/8"	1 3/16"	1 1/4"	1 3/8"	1 7/16"	1 1/2"	1 5/8"	1 3/4"	1 15/16"	T Nom.	L	P	
H609	2.50"	2.193"	9	1	x	x	x	-	-	-	-	-	-	-	-	.459"	1 3/16"	47/64"	.6	
H6010	2.76	2.427	10	1	x	x	x	x	x	-	-	-	-	-	-	.459	1 3/16	47/64	.8	
H6011	2.96	2.662	11	1	x	x	x	x	x	x	-	-	-	-	-	.459	1 3/16	47/64	1.0	
H6012	3.25	2.898	12	1	x	x	x	x	x	x	x	-	-	-	-	.459	1 3/16	47/64	1.3	
H6013	3.45	3.134	13	1	x	x	x	x	x	x	x	x	-	-	-	.459	1 3/16	47/64	1.5	
H6014	3.74	3.371	14	1	x	x	x	x	x	x	x	x	-	-	-	.459	1 3/16	47/64	1.7	
H6015	3.98	3.607	15	1	x	x	x	x	x	x	x	x	x	-	-	.459	1 3/16	47/64	2.0	
H6016	4.22	3.844	16	1	x	x	x	x	x	x	x	x	x	x	-	.459	1 3/16	47/64	2.5	
H6017	4.46	4.082	17	1	-	-	x	x	x	x	x	x	x	x	x	.459	1 3/16	47/64	2.7	
H6018	4.70	4.319	18	1	-	-	x	x	x	x	x	x	x	x	x	.459	1 3/16	47/64	3.4	
H6019	4.95	4.557	19	1	-	-	x	x	x	x	x	x	x	x	x	.459	1 3/16	47/64	4.1	
H6020	5.19	4.794	20	1	-	-	x	x	x	x	x	x	x	x	x	.459	1 3/16	47/64	3.9	
H6021	5.43	5.032	21	1	-	-	x	x	x	x	x	x	x	x	x	.459	1 3/16	47/64	5.4	
H6022	5.67	5.270	22	1	-	-	x	x	x	x	x	x	x	x	x	.459	1 3/16	47/64	5.7	
H6023	5.91	5.508	23	1	-	-	x	x	x	x	x	x	x	x	x	.459	1 3/16	47/64	6.0	
H6024	6.15	5.746	24	1	-	-	x	x	x	x	x	x	x	x	x	.459	1 3/16	47/64	6.3	
H6025	6.39	5.984	25	1	-	-	x	x	x	x	x	x	x	x	x	.459	1 3/16	47/64	6.5	
H6026	6.63	6.222	26	1	-	-	x	x	x	x	x	x	x	x	x	.459	1 3/16	47/64	6.8	
H6027	6.87	6.460	27	1	-	-	x	x	x	x	x	x	x	x	x	.459	1 3/16	47/64	7.1	
H6028	7.11	6.699	28	1	-	-	x	x	x	x	x	x	x	x	x	.459	1 3/16	47/64	7.4	
H6029	7.35	6.937	29	1	-	-	x	x	x	x	x	x	x	x	x	.459	1 3/16	47/64	7.4	
H6030	7.59	7.175	30	1	-	-	x	x	x	x	x	x	x	x	x	.459	1 3/16	47/64	8.0	
6032	8.07	7.652	32	1	-	-	x	-	-	x	-	x	x	-	x	.459	1 3/16	47/64	8.6	
6035	8.78	8.367	35	1	-	-	x	-	-	x	-	x	x	x	x	.459	1 3/16	47/64	9.5	
6036	9.02	8.605	36	1	-	-	x	-	-	x	-	x	x	-	x	.459	1 3/16	47/64	9.9	
6040	9.98	9.559	40	1	-	-	x	-	-	x	-	x	x	-	x	.459	1 3/16	47/64	11.5	
6045	11.18	10.752	45	1	-	-	x	-	-	x	x	x	-	-	x	.459	1 3/16	47/64	13.8	
6046	11.42	10.990	46	1	-	-	-	-	-	-	-	-	-	x	x	.459	1 3/16	47/64	14.2	
6076	18.55	18.149	76	1	-	-	-	-	-	-	-	-	-	x	x	.459	1 13/16	1 23/64	33.7	

↑ HARDENED TEETH ↓

All Stock Finished Bore Sprockets are furnished with Standard Keyway on Centerline of Tooth and Hallow Head Setscrew over Keyway. Sprockets with HARDENED TEETH have an additional Setscrew at 90° to Keyway.



TYPE 1



TYPE A



Table No. 2

Type "A" Steel Plate Sprockets

Part No.	Outside Dia.	Pitch Dia.	No. Teeth	Stock Bore	T (Nom.)	Wt. Lbs.	Part No.	Outside Dia.	Pitch Dia.	No. Teeth	Stock Bore	T (Nom.)	Wt. Lbs.
60A10	2.76"	2.427"	10	5/8"	.459"	.4	60A42	10.46"	10.036"	42	3/4"	.459"	9.9
60A11	3.00	2.662	11	5/8	.459	.5	60A43	10.70	10.275	43	3/4	.459	10.1
60A12	3.25	3.134	12	5/8	.459	.6	60A44	10.94	10.513	44	3/4	.459	10.6
60A13	3.45	3.134	13	5/8	.459	.7	60A45	11.18	10.752	45	3/4	.459	11.3
60A14	3.74	3.371	14	5/8	.459	.9	60A46	11.42	10.990	46	3/4	.459	11.8
60A15	3.98	3.607	15	5/8	.459	1.0	60A47	11.65	11.229	47	3/4	.459	12.3
60A16	4.22	3.844	16	5/8	.459	1.1	60A48	11.89	11.467	48	3/4	.459	12.6
60A17	4.46	4.082	17	5/8	.459	1.3	60A49	12.13	11.706	49	3/4	.459	13.2
60A18	4.70	4.319	18	5/8	.459	1.5	60A50	12.37	11.945	50	3/4	.459	13.8
60A19	4.95	4.557	19	3/4	.459	1.8	60A51	12.61	12.183	51	3/4	.459	14.4
60A20	5.19	4.794	20	3/4	.459	1.9	60A52	12.85	12.422	52	3/4	.459	15.0
60A21	5.43	5.032	21	3/4	.459	2.2	60A53	13.09	12.660	53	3/4	.459	15.5
60A22	5.67	5.270	22	3/4	.459	2.4	60A54	13.33	12.899	54	3/4	.459	16.1
60A23	5.91	5.508	23	3/4	.459	2.6	60A55	13.57	13.137	55	3/4	.459	16.7
60A24	6.15	5.746	24	3/4	.459	2.8	60A56	13.81	13.376	56	3/4	.459	17.3
60A25	6.39	5.984	25	3/4	.459	3.3	60A57	14.04	13.615	57	3/4	.459	18.0
60A26	6.53	6.222	26	3/4	.459	3.6	60A58	14.28	13.853	58	3/4	.459	18.6
60A27	6.87	6.460	27	3/4	.459	4.0	60A59	14.52	14.092	59	3/4	.459	19.3
60A28	7.11	6.699	28	3/4	.459	4.3	60A60	14.76	14.331	60	3/4	.459	19.9
60A29	7.35	6.937	29	3/4	.459	4.5	60A64	15.72	15.285	64	3/4	.459	22.7
60A30	7.59	7.175	30	3/4	.459	4.9	60A65	15.93	15.524	65	3/4	.459	23.4
60A31	7.83	7.413	31	3/4	.459	5.3	60A66	16.16	15.762	66	3/4	.459	24.1
60A32	8.07	7.652	32	3/4	.459	5.6	60A68	16.67	16.240	68	3/4	.459	25.6
60A33	8.30	7.890	33	3/4	.459	6.0	60A70	17.15	16.717	70	3/4	.459	27.1
60A34	8.54	8.129	34	3/4	.459	6.5	60A72	17.63	17.194	72	3/4	.459	28.7
60A35	8.78	8.367	35	3/4	.459	7.0	60A76	18.55	18.149	76	1	.459	33.9
60A36	9.02	8.605	36	3/4	.459	7.3	60A80	19.54	19.103	80	1	.459	37.3
60A37	9.26	8.844	37	3/4	.459	7.8	60A84	20.49	20.058	84	1	.459	39.9
60A38	9.50	9.082	38	3/4	.459	8.2	60A90	21.93	21.490	90	1	.459	44.9
60A39	9.74	9.321	39	3/4	.459	8.3	60A96	23.36	22.922	96	1	.459	52.4
60A40	9.98	9.559	40	3/4	.459	9.0	60A112	27.18	26.742	112	1	.459	68.5
60A41	10.22	9.798	41	3/4	.459	9.4							