



Table No. 1 **Steel Single Sprockets with Browning Split Taper® Bushings**



HARDENED TEETH

Part No.	Bushing	Bore Range	DIAMETERS		No. Teeth	Type	DIMENSIONS						Wt. Less Bushing
			Outside	Pitch			T Norm.	OL	L	P	C	H	
H60G10	G	3/8 - 1"	2.76"	2.427"	10	3	.459"	1 3/4"	1"	1 3/32"	9/16"	2"	.6
H60H11	H	3/8 - 1 1/2	2.96	2.662	11	3	.459	1 31/32	1 1/4	1 11/32	9/16	2 1/2	.7
H60H12	H	3/8 - 1 1/2	3.25	2.898	12	3	.459	1 13/16	1 1/4	1 3/16	13/32	2 1/2	.8
H60H13	H	3/8 - 1 1/2	3.45	3.134	13	3	.459	1 1/2	1 1/4	27/32	1/16	2 1/2	.8
H60P13	P1	1/2 - 1 3/4	3.45	3.134	13	4	.459	2 5/16	1 15/16	1 21/32	5/32	3	1.1
H60H14	H	3/8 - 1 1/2	3.74	3.371	14	3	.459	1 1/2	1 1/4	27/32	1/16	2 1/2	1.0
H60P14	P1	1/2 - 1 3/4	3.74	3.371	14	4	.459	2 3/16	1 15/16	1 15/32	0	3	1.2
H60H15	H	3/8 - 1 1/2	3.98	3.607	15	3	.459	1 1/2	1 1/4	27/32	1/16	2 1/2	1.2
H60P15	P1	1/2 - 1 3/4	3.98	3.607	15	4	.459	2 3/16	1 15/16	1 15/32	0	3	1.6
H60H16	H	3/8 - 1 1/2	4.22	3.844	16	3	.459	1 1/2	1 1/4	27/32	1/16	2 1/2	1.3
H60P16	P1	1/2 - 1 3/4	4.22	3.844	16	4	.459	2 3/16	1 15/16	1 15/32	0	3	2.0
H60H17	H	3/8 - 1 1/2	4.46	4.082	17	3	.459	1 1/2	1 1/4	27/32	1/16	2 1/2	1.5
H60P17	P1	1/2 - 1 3/4	4.46	4.082	17	4	.459	2 3/16	1 15/16	1 15/32	0	3	2.2
H60H18	H	3/8 - 1 1/2	4.70	4.319	18	3	.459	1 1/2	1 1/4	27/32	1/16	2 1/2	1.7
H60P18	P1	1/2 - 1 3/4	4.70	4.319	18	4	.459	2 3/16	1 15/16	1 15/32	0	3	2.4
H60H19	H	3/8 - 1 1/2	4.95	4.557	19	3	.459	1 1/2	1 1/4	27/32	1/16	2 1/2	1.9
H60P19	P1	1/2 - 1 3/4	4.95	4.557	19	4	.459	2 3/16	1 15/16	1 15/32	0	3	2.5
H60H20	H	3/8 - 1 1/2	5.19	4.794	20	3	.459	1 1/2	1 1/4	27/32	1/16	2 1/2	2.1
H60P20	P1	1/2 - 1 3/4	5.19	4.794	20	4	.459	2 3/16	1 15/16	1 15/32	0	3	3.0
H60Q20	Q1	3/4 - 2 11/16	5.19	4.794	20	4	.459	2 25/32	2 1/2	2 1/32	0	4 1/8	3.5
H60P21	P1	1/2 - 1 3/4	5.43	5.032	21	4	.459	2 3/16	1 15/16	1 15/32	0	3	3.0
H60Q21	Q1	3/4 - 2 11/16	5.43	5.032	21	4	.459	2 25/32	2 1/2	2 1/32	0	4 1/8	3.8
H60H22	H	3/8 - 1 1/2	5.67	5.270	22	3	.459	1 1/2	1 1/4	27/32	1/16	2 1/2	2.6
H60P22	P1	1/2 - 1 3/4	5.67	5.270	22	4	.459	2 3/16	1 15/16	1 15/32	0	3	3.3
H60Q22	Q1	3/4 - 2 11/16	5.67	5.270	22	4	.459	2 25/32	2 1/2	2 1/32	0	4 1/8	4.1
H60P23	P1	1/2 - 1 3/4	5.91	5.508	23	4	.459	2 3/16	1 15/16	1 15/32	0	3	3.5
H60Q23	Q1	3/4 - 2 11/16	5.91	5.508	23	4	.459	2 25/32	2 1/2	2 1/32	0	4 1/8	4.3
H60H24	H	3/8 - 1 1/2	6.15	5.746	24	3	.459	1 1/2	1 1/4	27/32	1/16	2 1/2	3.0
H60P24	P1	1/2 - 1 3/4	6.15	5.746	24	4	.459	2 3/16	1 15/16	1 15/32	0	3	3.9
H60Q24	Q1	3/4 - 2 11/16	6.15	5.746	24	4	.459	2 25/32	2 1/2	2 1/32	0	4 1/8	4.5
H60P25	P1	1/2 - 1 3/4	6.39	5.984	25	4	.459	2 3/16	1 15/16	1 15/32	0	3	4.3
H60Q25	Q1	3/4 - 2 11/16	6.39	5.984	25	4	.459	2 25/32	2 1/2	2 1/32	0	4 1/8	4.0
H60P26	P1	1/2 - 1 3/4	6.63	6.222	26	4	.459	2 3/16	1 15/16	1 15/32	0	3	4.3
H60Q26	Q1	3/4 - 2 11/16	6.63	6.222	26	4	.459	2 25/32	2 1/2	2 1/32	0	4 1/8	6.4
H60P27	P1	1/2 - 1 3/4	6.87	6.460	27	4	.459	2 3/16	1 15/16	1 15/32	0	3	4.6
H60Q27	Q1	3/4 - 2 11/16	6.87	6.460	27	4	.459	2 25/32	2 1/2	2 1/32	0	4 1/8	6.6
H60P28	P1	1/2 - 1 3/4	7.11	6.699	28	4	.459	2 3/16	1 15/16	1 15/32	0	3	5.0
H60Q28	Q1	3/4 - 2 11/16	7.11	6.699	28	4	.459	2 25/32	2 1/2	2 1/32	0	4 1/8	6.9
H60Q29	Q1	3/4 - 2 11/16	7.35	6.937	29	4	.459	2 25/32	2 1/2	2 1/32	0	4 1/8	7.3
H60P30	P1	1/2 - 1 3/4	7.59	7.175	30	4	.459	2 3/16	1 15/16	1 15/32	0	3	5.6
H60Q30	Q1	3/4 - 2 11/16	7.59	7.175	30	4	.459	2 25/32	2 1/2	2 1/32	0	4 1/8	7.7
60Q31	Q1	3/4 - 2 11/16	7.83	7.413	31	4	.459	2 25/32	2 1/2	2 1/32	0	4 1/8	7.8
60Q32	Q1	3/4 - 2 11/16	8.07	7.652	32	4	.459	2 25/32	2 1/2	2 1/32	0	4 1/8	8.3
60Q33	Q1	3/4 - 2 11/16	8.30	7.891	33	4	.459	2 25/32	2 1/2	2 1/32	0	4 1/8	8.7
60Q34	Q1	3/4 - 2 11/16	8.54	8.129	34	4	.459	2 25/32	2 1/2	2 1/32	0	4 1/8	9.1
60Q35	Q1	3/4 - 2 11/16	8.78	8.367	35	4	.459	2 25/32	2 1/2	2 1/32	0	4 1/8	9.3
60Q36	Q1	3/4 - 2 11/16	9.02	8.605	36	4	.459	2 25/32	2 1/2	2 1/32	0	4 1/8	9.9
60Q37	Q1	3/4 - 2 11/16	9.26	8.844	37	4	.459	2 25/32	2 1/2	2 1/32	0	4 1/8	10.3
60Q38	Q1	3/4 - 2 11/16	9.50	9.082	38	4	.459	2 25/32	2 1/2	2 1/32	0	4 1/8	10.6
60Q39	Q1	3/4 - 2 11/16	9.74	9.321	39	4	.459	2 25/32	2 1/2	2 1/32	0	4 1/8	11.1
60Q40	Q1	3/4 - 2 11/16	9.98	9.559	40	4	.459	2 25/32	2 1/2	2 1/32	0	4 1/8	11.6
60Q41	Q1	3/4 - 2 11/16	10.22	9.798	41	4	.459	2 25/32	2 1/2	2 1/32	0	4 1/8	11.9
60Q42	Q1	3/4 - 2 11/16	10.46	10.036	42	4	.459	2 25/32	2 1/2	2 1/32	0	4 1/8	12.6
60Q44	Q1	3/4 - 2 11/16	10.94	10.513	44	4	.459	2 25/32	2 1/2	2 1/32	0	4 1/8	13.4
60Q45	Q1	3/4 - 2 11/16	11.18	10.752	45	4	.459	2 25/32	2 1/2	2 1/32	0	4 1/8	13.9
60Q47	Q1	3/4 - 2 11/16	11.65	11.229	47	4	.459	2 25/32	2 1/2	2 1/32	0	4 1/8	16.3
60Q48	Q1	3/4 - 2 11/16	11.89	11.467	48	4	.459	2 25/32	2 1/2	2 1/32	0	4 1/8	16.4
60Q50	Q1	3/4 - 2 11/16	12.37	11.945	50	4	.459	2 25/32	2 1/2	2 1/32	0	4 1/8	16.9
60Q54	Q1	3/4 - 2 11/16	13.33	12.899	54	4	.459	2 25/32	2 1/2	2 1/32	0	4 1/8	19.6
60Q56	Q1	3/4 - 2 11/16	13.81	13.376	56	4	.459	2 25/32	2 1/2	2 1/32	0	4 1/8	20.3
60Q60	Q1	3/4 - 2 11/16	14.73	14.331	60	4	.459	2 25/32	2 1/2	2 1/32	0	5 3/8	22.9
60Q70	Q1	3/4 - 2 11/16	17.12	16.717	70	4	.459	2 25/32	2 1/2	2 1/32	0	4 1/8	30.9
60R70	R1	1 1/8 - 3 3/4	17.12	16.717	70	4	.459	3 5/32	2 7/8	2 13/32	0	5 3/8	31.8
60Q72	Q1	3/4 - 2 11/16	17.63	17.194	72	4	.459	2 25/32	2 1/2	2 1/32	0	4 1/8	31.9
60R72	R1	1 1/8 - 3 3/4	17.63	17.194	72	4	.459	3 5/32	2 7/8	2 13/32	0	5 3/8	34.1
60Q80	Q1	3/4 - 2 11/16	19.54	19.103	80	4	.459	2 25/32	2 1/2	2 1/32	0	4 1/8	39.1
60R80	R1	1 1/8 - 3 3/4	19.54	19.103	80	4	.459	3 5/32	2 7/8	2 13/32	0	5 3/8	41.5
60Q84	Q1	3/4 - 2 11/16	20.49	20.058	84	4	.459	2 25/32	2 1/2	2 1/32	0	4 1/8	41.6
60R84	R1	1 1/8 - 3 3/4	20.49	20.058	84	4	.459	3 5/32	2 7/8	2 13/32	0	5 3/8	44.8
60Q96	Q1	3/4 - 2 11/16	23.36	22.922	96	4	.459	2 25/32	2 1/2	2 1/32	0	4 1/8	54.0
60R96	R1	1 1/8 - 3 3/4	23.36	22.922	96	4	.459	3 5/32	2 7/8	2 13/32	0	5 3/8	56.0
60Q112	Q1	3/4 - 2 11/16	27.18	26.742	112	4	.459	2 25/32	2 1/2	2 1/32	0	4 1/8	73.0
60R112	R1	1 1/8 - 3 3/4	27.18	26.742	112	4	.459	3 5/32	2 7/8	2 13/32	0	5 3/8	74.5

Where two sprockets with the same number of teeth but different bushings are offered, we suggest using the one with the larger bushing for heavier service drives.