



### Sprockets for **No. 120**, 1 1/2" Pitch ANSI Chain

Table No. 1 Steel Minimum Bore Double Sprockets

Part No.	DIAMETERS		No. Teeth	Type	BORE		DIMENSIONS					Wt. Lbs
	Outside	Pitch			Stock	Max.*	T	M	L Max.	P	H	
D120B11	6.01"	5.324"	11	DB	1 1/2"	2 3/8"	.894"	2.683"	3 3/4"	1 1/16"	3 9/16"	13.7
D120B12	6.50	5.796	12	DB	1 1/2	2 3/4	.894	2.683	3 3/4	1 1/16	4 1/16	17.4
D120B13	6.99	6.268	13	DB	1 1/2	3	.894	2.683	3 3/4	1 1/16	4 9/16	21.6
D120B14	7.47	6.741	14	DB	1 1/2	3 5/16	.894	2.683	3 3/4	1 1/16	5	25.8
D120B15	7.96	7.215	15	DB	1 1/2	3 3/4	.894	2.683	3 3/4	1 1/16	5 1/2	31.0
D120B16	8.39	7.689	16	DB	1 1/2	3 3/4	.894	2.683	3 3/4	1 1/16	5 1/2	34.6
D120B17	8.88	8.163	17	DB	1 1/2	3 3/4	.894	2.683	3 3/4	1 1/16	5 1/2	38.2
D120B18	9.41	8.638	18	DB	1 1/2	3 3/4	.894	2.683	3 3/4	1 1/16	5 3/4	44.6
D120B19	9.89	9.113	19	DB	1 1/2	3 3/4	.894	2.683	3 3/4	1 1/16	5 3/4	49.0
D120B20	10.37	9.589	20	DB	1 1/2	3 3/4	.894	2.683	3 3/4	1 1/16	5 3/4	55.0
D120B21	10.85	10.064	21	DB	1 1/2	3 3/4	.894	2.683	3 3/4	1 1/16	5 3/4	60.3
D120B22	11.33	10.540	22	DB	1 1/2	3 3/4	.894	2.683	4	1 5/16	5 3/4	67.6
D120B23	11.81	11.016	23	DB	1 1/2	4 1/2	.894	2.683	4	1 5/16	6 1/2	76.1
D120B24	12.29	11.492	24	DB	1 1/2	4 1/2	.894	2.683	4	1 5/16	6 1/2	82.2
D120B25	12.77	11.968	25	DB	1 1/2	4 1/2	.894	2.683	4	1 5/16	6 1/2	88.6
D120B26	13.25	12.444	26	DB	1 1/2	4 1/2	.894	2.683	4	1 5/16	6 1/2	95.2
D120B30	15.17	14.350	30	DB	1 1/2	4 1/2	.894	2.683	4	1 5/16	6 1/2	124
D120C35	17.57	16.734	35	DC	1 1/2	5 3/8	.894	2.683	6	1 21/32	7 1/2	195
D120C45	22.35	21.503	45	DC	1 1/2	5 3/8	.894	2.683	6	1 21/32	7 1/2	301
D120C60	29.52	28.661	60	DC	1 1/2	5 3/8	.894	2.683	6	1 21/32	9 1/2	361

\* Maximum bores shown will accommodate standard keyway and setscrew over keyway. Slightly larger bores are possible with no keyway, shallow keyway or setscrew at angle to keyway. These sprockets are furnished with minimum bore and no keyway. They can be rebored to size, keywayed and setscrewed for a reasonable extra charge.



### Sprockets for **No. 140**, 1 3/4" Pitch ANSI Chain

Table No. 2 Steel Single Sprockets with Browning Split Taper® Bushings

Part No.	Bushing	Bore Range	DIAMETERS		No. Teeth	Type	DIMENSIONS						Wt. Less Bushing
			Outside	Pitch			T Nom.	OL	L	P	C	H	
H140Q11	Q1	3/4 - 2 11/16"	7.01"	6.212"	11	4	.924"	2 25/32"	2 1/2"	1 9/16"	0	4 1/8"	6.4
H140Q12	Q1	3/4 - 2 11/16"	7.58	6.762	12	4	.924	2 25/32	2 1/2	1 9/16	0	4 1/8	9.0
H140R13	R1	1 1/8 - 3 3/4	8.15	7.313	13	4	.924	3 5/32	2 7/8	1 15/16	0	5 3/8	11.1
H140R14	R1	1 1/8 - 3 3/4	8.72	7.864	14	4	.924	3 5/32	2 7/8	1 15/16	0	5 3/8	12.6
H140R15	R1	1 1/8 - 3 3/4	9.28	8.417	15	4	.924	3 5/32	2 7/8	1 15/16	0	5 3/8	14.7
H140R16	R1	1 1/8 - 3 3/4	9.85	8.970	16	4	.924	3 5/32	2 7/8	1 15/16	0	5 3/8	16.5
H140R17	R1	1 1/8 - 3 3/4	10.41	9.524	17	4	.924	3 5/32	2 7/8	1 15/16	0	5 3/8	18.5
H140R18	R1	1 1/8 - 3 3/4	10.97	10.078	18	4	.924	3 5/32	2 7/8	1 15/16	0	5 3/8	20.5
H140R19	R1	1 1/8 - 3 3/4	11.54	10.632	19	4	.924	3 5/32	2 7/8	1 15/16	0	5 3/8	23.0
H140R20	R1	1 1/8 - 3 3/4	12.10	11.187	20	4	.924	3 5/32	2 7/8	1 15/16	0	5 3/8	25.4
H140R21	R1	1 1/8 - 3 3/4	12.66	11.742	21	4	.924	3 5/32	2 7/8	1 15/16	0	5 3/8	27.8
H140R22	R1	1 1/8 - 3 3/4	13.22	12.297	22	5	.924	3 5/32	2 7/8	7/8	1 1/16	5 3/8	32.5
H140R23	R1	1 1/8 - 3 3/4	13.78	12.852	23	5	.924	3 5/32	2 7/8	7/8	1 1/16	5 3/8	36.0
H140R24	R1	1 1/8 - 3 3/4	14.34	13.407	24	5	.924	3 5/32	2 7/8	7/8	1 1/16	5 3/8	37.6
H140R25	R1	1 1/8 - 3 3/4	14.90	13.963	25	5	.924	3 5/32	2 7/8	7/8	1 1/16	5 3/8	40.3
H140R26	R1	1 1/8 - 3 3/4	15.46	14.518	26	5	.924	3 5/32	2 7/8	7/8	1 1/16	5 3/8	44.0
H140R30	R2	1 3/8 - 3 5/8	17.70	16.742	30	6	.924	5 5/32	4 7/8	7/8	2	5 3/8	68.0
140R35	R2	1 3/8 - 3 5/8	20.49	19.523	35	6	.924	5 5/32	4 7/8	7/8	2	5 3/8	88.0
140R36	R2	1 3/8 - 3 5/8	21.05	20.079	36	6	.924	5 5/32	4 7/8	7/8	2	5 3/8	90.0
140S36	S1	1 11/16 - 4 1/4	21.05	20.079	36	5	.924	4 3/4	4 3/8	1 1/16	2 3/8	6 3/8	89.0
140R40	R2	1 3/8 - 3 5/8	23.29	22.305	40	6	.924	5 5/32	4 7/8	7/8	2	5 3/8	109
140S40	S1	1 11/16 - 4 1/4	23.29	22.305	40	5	.924	4 3/4	4 3/8	1 1/16	2 3/8	6 3/8	107
140S45	S1	1 11/16 - 4 1/4	26.08	25.087	45	5	.924	4 3/4	4 3/8	1 1/16	2 3/8	6 3/8	132
140S48	S2	1 7/8 - 4 3/16	27.75	26.757	48	6	.924	7 1/2	6 3/4	2 15/16	2 7/8	6 3/8	169
140S54	S2	1 7/8 - 4 3/16	31.10	30.097	54	6	.924	7 1/2	6 3/4	2 15/16	2 7/8	6 3/8	208
140S60	S2	1 7/8 - 4 3/16	34.44	33.438	60	6	.924	7 1/2	6 3/4	2 15/16	2 7/8	6 3/8	230
140S70	S2	1 7/8 - 4 3/16	40.02	39.006	70	6	.924	7 1/2	6 3/4	2 15/16	2 7/8	6 3/8	311
140S80	S2	1 7/8 - 4 3/16	45.59	44.575	80	6	.924	7 1/2	6 3/4	2 15/16	2 7/8	6 3/8	242

