


Table No. 1 Sprockets for **No. 40**, 1/2" Pitch ANSI Chain

Part No.	Bushing	Bore Range	Diameter		No. of Teeth	Type	T Nom.	L	H	Wt. Lbs. Less Bush.
			Outside	Pitch						
H40TB14	1008	1/2 - 1	2.49	2.247	14	1	.284	7/8	1 13/16	0.3
H40TB15	1008	1/2 - 1	2.65	2.405	15	1	.284	7/8	1 13/16	0.4
H40TB16	1008	1/2 - 1	2.81	2.563	16	1	.284	7/8	1 15/16	0.5
H40TB17	1210	1/2 - 1 1/4	2.97	2.721	17	1	.284	1	2 3/8	0.3
H40TB18	1210	1/2 - 1 1/4	3.14	2.879	18	1	.284	1	2 15/32	0.4
H40TB19	1210	1/2 - 1 1/4	3.30	3.038	19	1	.284	1	2 15/32	0.7
H40TB20	1610	1/2 - 1 5/8	3.46	3.196	20	1	.284	1	2 25/32	0.6
H40TB21	1610	1/2 - 1 5/8	3.62	3.355	21	1	.284	1	2 25/32	0.8
H40TB22	1610	1/2 - 1 5/8	3.78	3.513	22	1	.284	1	2 25/32	0.8
H40TB23	1610	1/2 - 1 5/8	3.94	3.672	23	1	.284	1	3	0.9
H40TB24	1610	1/2 - 1 5/8	4.10	3.831	24	1	.284	1	3 1/4	1.0
H40TB25	1610	1/2 - 1 5/8	4.26	3.989	25	1	.284	1	3 1/4	1.1
H40TB26	1610	1/2 - 1 5/8	4.42	4.148	26	1	.284	1	3 1/4	1.1
H40TB28	1610	1/2 - 1 5/8	4.74	4.466	28	1	.284	1	3	1.4
H40TB30	1610	1/2 - 1 5/8	5.06	4.783	30	1	.284	1	3	1.6
40TB32	1610	1/2 - 1 5/8	5.38	5.101	32	1	.284	1	3	1.8
40TB35	1610	1/2 - 1 5/8	5.86	5.578	35	1	.284	1	3	2.0
40TB36	1610	1/2 - 1 5/8	6.02	5.737	36	1	.284	1	3	2.1
40TB40	1610	1/2 - 1 5/8	6.65	6.373	40	1	.284	1	3	2.5
40TB42	1610	1/2 - 1 5/8	6.97	6.691	42	1	.284	1	3	2.7
40TB45	1610	1/2 - 1 5/8	7.45	7.168	45	1	.284	1	3	3.1
40TB48	1610	1/2 - 1 5/8	7.93	7.645	48	1	.284	1	3	4.1
40TB54	1610	1/2 - 1 5/8	8.88	8.599	54	1	.284	1	3	5.0
40TB60	1610	1/2 - 1 5/8	9.84	9.554	60	1	.284	1	3	6.0
40TB70	2012	1/2 - 2	11.43	11.145	70	1	.284	1 1/4	3 7/8	7.3
40TB72	2012	1/2 - 2	11.75	11.463	72	1	.284	1 1/4	3 7/8	7.5
40TB80	2012	1/2 - 2	13.03	12.736	80	1	.284	1 1/4	3 7/8	8.3
40TB84	2012	1/2 - 2	13.66	13.372	84	1	.284	1 1/4	3 7/8	10.2
40TB96	2012	1/2 - 2	15.57	15.282	96	1	.284	1 1/4	3 7/8	15.3
40TB112	2517	1/2 - 2 1/2	18.12	17.828	112	1	.284	1 3/4	4 5/8	21.5



Type 3

Table No. 2 Steel Double Sprockets

Part No.	Bushing	Bore Range	Diameter		No. of Teeth	Type	T (Nom.)	L	H	Wt. Lbs. Less Bush.
			Outside	Pitch						
D40TBA15	1008	1/2 - 1	2.65	2.405	15	3	.275	7/8	-	0.4
D40TBA16	1008	1/2 - 1	2.81	2.563	16	3	.275	7/8	-	0.5
D40TBA17	1008	1/2 - 1	2.97	2.721	17	3	.275	7/8	-	0.8
D40TB18	1210	1/2 - 1 1/4	3.14	2.879	18	2	.275	1	2 11/16	0.6
D40TB19	1210	1/2 - 1 1/4	3.30	3.038	19	2	.275	1	2 1/2	0.8
D40TB20	1610	1/2 - 1 5/8	3.46	3.196	20	2	.275	1	2 21/32	0.9
D40TB21	1610	1/2 - 1 5/8	3.62	3.355	21	2	.275	1	2 53/64	1.0
D40TB23	1610	1/2 - 1 5/8	3.94	3.672	23	2	.275	1	3 9/64	1.3
D40TB25	2012	1/2 - 2	4.26	3.989	25	2	.275	1 1/4	3 15/32	1.1
D40TB30	2012	1/2 - 2	5.06	4.783	30	2	.275	1 1/4	4 17/64	2.9
D40TB36	2012	1/2 - 2	6.02	5.737	36	2	.275	1 1/4	5 1/8	5.3
D40TB42	2517	1/2 - 2 1/2	6.97	6.691	42	2	.275	1 3/4	4 1/4	7.0
D40TB48	2517	1/2 - 2 1/2	7.93	7.645	48	2	.275	1 3/4	4 1/4	9.6
D40TB52	2517	1/2 - 2 1/2	8.57	8.281	52	2	.275	1 3/4	4 1/4	11.4
D40TB60	2517	1/2 - 2 1/2	9.84	9.554	60	2	.275	1 3/4	4 1/4	15.4
D40TB68	2517	1/2 - 2 1/2	11.11	10.826	68	2	.275	1 3/4	4 1/4	20.5
D40TB76	2517	1/2 - 2 1/2	12.39	12.099	76	2	.275	1 3/4	4 1/4	25.7
D40TB84	2517	1/2 - 2 1/2	13.66	13.372	84	2	.275	1 3/4	4 1/4	31.6

