


Browning® Mounted Ball Bearings



Duty: Light
Rolling Elements: Ball
Outer: Cylindrical O.D.
Self Alignment: +/- 1.5 Degrees
Lock: Setscrew
Seal: Contact
Temperature: -20° to 200°F
Relube: No



SLS 100 Series Light Duty Straight OD Inserts - Setscrew Locking

Bore Diameter inch	Part No.	Basic Dynamic Rating lb/N	Dimensions inch / mm						Max. Rad. To Clear	Setscrew Thread	Unit Wt. lb/kg
			A	D	E	G	J	L			
1/2	SLS-108	2108	1.5748	5/8	33/64	5/32	15/16	31/32	.055	10-32	.4
5/8	SLS-110	9377	40	15.9	13.1	4.0	23.8	24.6	1.4		.18
3/4	SLS-112	2611 11614	1.8504 47	23/32 18.3	19/32 15.1	3/16 4.8	1 1/16 27.0	1 3/16 30.2	0.07 1.8	1/4-28	.5 .23
7/8	SLS-114	2801	2.042	49/64	19/32	3/16	1 7/64	1 3/8	0.07	1/4-28	.6
15/16	SLS-115	12459	52	19.4	15.1	4.8	28.2	34.9	1.8		.27
1	SLS-116										
1 1/8	SLS-118	4381	2.4409	25/32	45/64	7/32	1 5/32	1 19/32	0.08	1/4-28	1.0
1 3/16	SLS-119	19487	62	19.8	17.9	5.6	29.4	40.5	2.0		.45
1 1/4	SLS-120S										
1 1/4	SLS-120	5782	2.8346	55/64	3/4	1/4	1 9/32	1 55/64	0.08	5/16-24	1.6
1 3/8	SLS-122	25718	72	21.8	19.1	6.4	32.5	47.2	2.0		.73
1 7/16	SLS-123										
1 1/2	SLS-124	7340 32648	3.1496 80	15/16 23.8	55/64 21.8	9/32 7.1	1 27/64 36.1	2 1/16 52.4	0.095 2.4	5/16-24	1.8 .82

Outside diameter may be oversized due to seal press fit.

Metric dimensions for reference only.

Not all parts are available from stock. Please contact customer service for availability (800) 626-2120.

For more information on bearing capabilities outside of our standard offering, please contact Application Engineering (800) 626-2093.