

Cayce™

Adjustable rubber nosepiece

Slim temple design

Wraparound coverage for superior protection

Available in a Carhartt polybag



CHB910ST •• (polybag)
Clear Anti-fog Lens with Black Frame



CHB918ST •• (polybag)
Sandstone Bronze Anti-fog Lens with Black Frame



CHB920ST •• (polybag)
Gray Anti-fog Lens with Black Frame



Polybag



There's more to see at
PYRAMEXSAFETY.COM
(P) 800.736.8673 | (F) 901.861.4967

All safety eyewear meets ANSI Z87.1+ standards (•) and provides 99% protection from harmful UV rays. All lenses are hard coated polycarbonate scratch-resistant. Some options meet Canadian CSA Z94.3 (•) – SEI third-party certification. For specific lens options, visit our website or contact your sales representative.

Cayce™

General Specifications

Weight: 25 gm
 Lens base: 7 curve
 Lens size diagonal: 136.2 mm
 Lens size vertical: 43.9 mm
 Lens thickness: 2.2 mm
 Overall length (lens - tip): 169.3 mm
 Overall width (hinge - hinge): 143.2 mm
 Closest point between temple tips: 78 mm

Materials

Lens: polycarbonate (PC)
 Frame: polycarbonate (PC)
 Temple: polycarbonate (PC)
 Temple tips: polyvinyl chloride (PVC)
 Screw: stainless steel
 Nosepiece: polyvinyl chloride (PVC)

Part No.

Lens Marking

Frame Marking

Part No.	Lens Marking	Frame Marking
CHB910ST	P +	P Z87 + / P c SEI CAN/CSA Z94.3-15
CHB918ST	P + S	P Z87 + / P c SEI CAN/CSA Z94.3-15
CHB920ST	P + S	P Z87 + / P c SEI CAN/CSA Z94.3-15

Lens Marking Symbols

P: Manufacturer's mark
 +: High impact
 S: Special purpose

Frame Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 c SEI CAN/CSA Z94.3-15: CAN/CSA standard for eye and face protection devices

