

Product Specifications



Fluorescent Green Construction Marking Paint

Part number 248

Category number 6180

UPC 88193002483

Construction Marking Paint is the premium paint offering from L.H Dottie. It is packaged in a can that can only be operated in an upside down position and is formulated to meet a variety of marking applications. It is designed to adhere to most surfaces including pavement, gravel and soil.



Physical Characteristics

| | |
|------------|----------------------------|
| Type | Construction Marking Paint |
| Resin Type | Alkyd |
| Color | Fluorescent Green |

Packaging Details

| | |
|-----------------------|------------------|
| Container | Inverted Aerosol |
| Aerosol Can Size (oz) | 20 oz |
| Standard Qty | 1 |
| Master Qty | 12 |
| Price Per | 1 |
| Package Length | 11.02 |
| Package Width | 8.35 |
| Package Height | 10.24 |
| Volume | 17 oz (net) |
| Package Weight | 1.33 |

Performance Data

| | |
|-----------------------|---------------|
| Flammability | Flammable |
| Flash Point | < -0°F |
| Operating Temperature | 40°F to 100°F |

Special Features

High Quality, Excellent Visibility & Durability, 3 Month Mark Performance, 548' Linear Coverage (Coverage Varies Depending on Width of Mark and Hide Desired)

| | |
|--------------------|--------|
| Dry Time Tack Free | 45 Min |
| Dry Time (min) | 30 Min |

Certifications

| | |
|--------------------|----------------------------------|
| RoHS Compliant | Yes |
| Industry Standards | Colors Meet OSHA & APWA/One Call |