

Eaton BR1224L125

Catalog Number: BR1224L125

Eaton Eaton BR main lug loadcenter ,No feed-thru lugs,Main lug,200 A,D1R,Aluminum,Cover included,NEMA 3R,Metallic,25 kAIC,BWH,NEMA 3R,40 Circuits,Twenty-four pole,30 Spaces,Three-wire

General specifications



Product Name	Catalog Number
Eaton BR main lug loadcenter	BR1224L125
UPC	Product Length/Depth
786676446556	3.88 in
Product Height	Product Width
16.75 in	14.31 in
Product Weight	Warranty
15.6 lb	10 year
Certifications	Catalog Notes
UL 67 UL 50	Suitable for use as service equipment when no more than 6 main disconnecting means are provided or when not used as lighting & appliance panelboard. Has notch for brhdk125 hold-down kit.

Product specifications

Number of spaces

12

Special features

No feed-thru lugs, includes BREQS125 hold-down screw

Interrupt rating

10 kAIC

Phase

Single-phase

Wire size

#6-2/0 AWG Cu/Al

Bus material

Aluminum

Main circuit breaker

BR

Enclosure

NEMA 1

Amperage Rating

125 A

Mounting

Combination

Enclosure material

Metallic

Type

Main lug

Cover

Cover included

Used with

Type BR 1-inch breakers

Number of wires

3

Number of circuits

24

Voltage rating

120/240V

Resources

Brochures

Loadcenters and Circuit Breakers

Type BR Arc Fault Circuit Breakers and Loadcenters

Catalogs

Eaton's Volume 1—Residential and Light Commercial

Drawings

Dimensional Drawing - BR 1 LOADCENTER, MAIN LUG ONLY, INDOOR
NEMA 1, 120/240 VAC, 1 PHASE

Installation instructions

Cutler-Hammer Type CH and BR Loadcenters - Instructions

Specifications and datasheets

Eaton Specification Sheet - BR1224L125

Box size

B1



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)