

Eaton BR24L125RP

Catalog Number: BR24L125RP

Eaton BR main lug loadcenter,Current design, Rainproof panels are furnished with hub closure plates,Main lug,125 A,6R,Aluminum,Cover included,NEMA 3R,Metallic,10 kAIC,4 Circuits,2 Spaces,Three-wire,Single-phase



General specifications

Product Name	Catalog Number
Eaton BR main lug loadcenter	BR24L125RP
UPC	Product Length/Depth
786676001502	13 in
Product Height	Product Width
4.7 in	7.2 in
Product Weight	Warranty
6.45 lb	10 year
Certifications	Catalog Notes
UL 50	Ground bar kit priced separately.
UL 67	Suitable for use as service equipment when no more than 2 service disconnecting mains are provided or when not used as lighting & appliance panelboard

Product specifications

Number of spaces

2

Special features

Current design

Interrupt rating

10 kAIC

Phase

Single-phase

Wire size

#14-1/0 AWG Cu/Al

Bus material

Aluminum

Enclosure

NEMA 3R

Amperage Rating

125 A

Number Of Poles

Four-pole

Enclosure material

Metallic

Type

Main lug

Cover

Cover included

Used with

Type BR 1-inch breakers

Number of wires

3

Number of circuits

4

Voltage rating

120/240 V

Box size

6R

Resources

Brochures

[Loadcenters and Circuit Breakers](#)

[Type BR Arc Fault Circuit Breakers and Loadcenters](#)

Catalogs

[Eaton's Volume 1—Residential and Light Commercial](#)

Installation instructions

[Cutler-Hammer Type CH and BR Loadcenters - Instructions](#)

Specifications and datasheets

[Eaton Specification Sheet - BR24L125RP](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)