

# Eaton XTCE040D00A

Catalog Number: XTCE040D00A

Eaton XT IEC contactor, 40A, 110 Vac 50 Hz, 120 Vac 60 Hz, ONO-0NC, 40A, Frame D, 55 mm, 50-60 Hz, 3, 5, 7.5/ 10, 15, 30, 40 hp(1/3PH@115, 200, 230/200, 230, 460, 575 V), Three-pole, , Screw terminals, FVNR



## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton XT IEC contactor	XTCE040D00A
<b>EAN</b>	<b>Product Length/Depth</b>
4015082777630	6.25 in
<b>Product Height</b>	<b>Product Width</b>
2.5 in	5 in
<b>Product Weight</b>	<b>Compliances</b>
2.05 lb	CE Marked RoHS Compliant
<b>Certifications</b>	<b>Catalog Notes</b>
UL Listed CSA Certified IEC 60947 EN 60947	Screw terminals (6-65A); 5 mm (80-150A); no lugs (185-2000A)

## defaultTaxonomyAttributeLabel

### Amperage Rating

40A

### HP rating - max

3, 5, 7.5/ 10, 15, 30, 40 hp (1/3PH  
@ 115,200,230/200,230,460,575 V)

### Number Of Poles

Three-pole

### Type

Full voltage non-reversing contactor

### Frequency rating

50-60 Hz

### Frame size

55 mm

### Terminals

Screw terminals

### Coil

110-120 Vac, 50/60 Hz

### Coil voltage

110-120 Vac, 50/60 Hz

### Contact configuration

0 NO, 0 NC

### Continuous ampere rating

40 A

### Series

XT IEC

### Operation

Non-reversing

## Resources

### Catalogs

Eaton's Volume 5—Motor Control and Protection

### Drawings

XTCE\_D AutoCAD 2D Footprint

XTCE\_D 2D Drawing Xchange

XTCE\_D 3D Inventor

XTCE\_D 3D Model Xchange

XTCE\_D 2D PDF

### Specifications and datasheets

Global Data Sheet - XTCE040D00A

Eaton Specification Sheet - XTCE040D00A



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)