



**SKU:** 79-006N

**UPC:** 0032076790066

**Features & Benefits:**

**Description:** Wire-Aide Wire-Pulling Lubricant, Non-Toxic, Slick Waxy Formula, Suitable for Fiber Optic Wire, 1 qt. Bottle

## Specs

### Additional Class Attributes

Base	Modified Wax
Shelf Life	Indefinite

### Additional Technical Specifications

Abrasion Protection	Excellent
Cling Ability	Excellent
Corrosion Test	Non-Corrosive
Drying Condition	Waxy film
Flash Point	Non-combustible
Freeze Thaw Stability	3-Cycles
Hardening Character	Non-hardening
Lubricity	Excellent
pH	6.5 - 7.0
Removal	Soap and water
Staining Properties	Non-staining
Viscosity	66,000 - 94,000 cps. at 10 rpm
Water Resistance	Repels water to some extent

### General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 4
NEMA Code	0-000-1
UPC Code	03207679006

### Testing Standards

Prop65 Compliance	WARNING: Cancer and Reproductive Harm - <a href="http://www.P65warnings.ca.gov">www.P65warnings.ca.gov</a>
-------------------	------------------------------------------------------------------------------------------------------------

### Color

Color	Yellow
-------	--------

**Environment and Temperature**

**Freezing Point**

28°F