



SKU: HST-250

UPC: 0032076562502

Features & Benefits:

Description: Polyolefin Heat Shrink Tubing, 2:1 Shrink Ratio 1/4 in. (6.4 mm) Dia. to 1/8 in (3.8mm) Dia., 4 In. Long, Black, (6/Pkg)

Specs

Additional Class Attributes

Includes	6 heat shrink tubes
Shrink Ratio	2:1
UV resistant	Yes
Warranty	1 Year

Dimensions

Expanded ID (IN)	0.25
Expanded ID (mm)	6.35
Recovered ID (IN)	0.125 IN

Additional Technical Specifications

Dielectric Strength	600 V/Mil
Water Resistance	Water resistant

Material and Finish

Insulation	Polyolefin
Material	Polyolefin

Conductor Ranges

Conductor Range CU Solid (Primary, run, main, line)	10 Sol - 18 Sol
Conductor Range CU Stranded (Primary, run, main, line)	10 Str - 18 Str

Testing Standards

Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
-------------------	--

Color

Color	Black
-------	-------

Voltage

Voltage Rating	600 V
----------------	-------

Environment and Temperature

Environmental Conditions	Indoor/Outdoor
Flammability Rating	Self-extinguishing within 30 seconds. Will not drip, flow, or crack.

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 10
UPC Code	03207656250