




Standard Construction Features

Belt Type: Banded PowerBand
 Core Material: Oil & Heat Resistant (chloroprene)
 Cord/Tensile: Polyester
 BandPly 1: Oil & Heat Resistant Standard
 BandPly 2: Oil & Heat Resistant Standard



Belt Section

Cross Section	Effective Length (in)	TW _S (in)	TH (in)	TW _T (in)	Strands
3V-PB	71.00 +0.40 -0.40	13/32	5/16	1 1/2	4

Measuring Information

* T (lb) is per belt/rib/strand

Y (in)	T* (lb)	G min (in)	W (in)	Angle (°)	O.D. (in)	O.C. (in)	Max Ride (in)	S (in)
29.500 +0.200 -0.200	100	0.34	0.35	38	3.820	12.000	0.20	0.406

Reference RMA IP-22-1991 for the industry standard governing this belt.



DesignView™
 Version 1.0 -
 Belt Information Sheet

Created 23 Jun 2017 by Gates

Created for
Super HC - 3V-PB

Gates Product Number
9385-4071

Customer Part Number
4/3V710

The length shall be measured by placing the belts on two sheaves of equal diameters that have been grooved in accordance with standard specifications and rotated at least three complete turns with the specified tension so that each strand receives half the total tension. The length will be that length obtained by adding the Reference Circumference of one sheave at dimension 'W' to twice the center distance (dimension 'Y').