



GE  
Lighting

### 63888 - GE286MAX-HO-N

#### GE Multi-Volt ProLine™ Electronic T8 High Output Fluorescent Lamps Ballast

- Line Voltage: Multi-Voltage 120 to 277 VAC, +/-10%, 50-60Hz
- Parallel lamp operation means system maintenance is easier to manage
- Instant Start
- Active Power Factor Correction
- No PCB's
- UL Listed (Class P, Type 1 Outdoor)
- Type HL
- Remote Mounting: 18 ft. max. lead length, 18 AWG min wire size



#### GENERAL CHARACTERISTICS

Lamp Type	Fluorescent -
Bulb	Electronic
Ballast Type	T8 High Output Fluorescent Lamps
Starting Method	Instant start
Lamp Wiring	Parallel
Line Voltage Regulation (+/-)	10.0 %
Ambient Temperature (MIN)	-22.0 °F
Ambient Temperature (MAX)	105.0 °F
Case Temperature (MAX)	90.0 °C
Ballast Factor	Normal
Power Factor Correction	Linear Fluorescent
Sound Rating	A (20-24 decibels)
Enclosure Type	Metal

#### ELECTRICAL CHARACTERISTICS

Supply Current Frequency (MIN)	50.0 Hz
Supply Current Frequency	60.0 Hz

#### DIMENSIONS

Exit Type	
Remote Mounting Distance	18.0 ft
Remote Mounting Wire Gauge	18.0 AWG

#### PRODUCT INFORMATION

Product Code	63888
Description	GE286MAX-HO-N
Standard Package	Case
Standard Package GTIN	10043168638880
Standard Package Quantity	10
Sales Unit	Master
No Of Items Per Sales Unit	10
No Of Items Per Standard Package	10
UPC	043168638883

#### CAUTIONS & WARNINGS

##### Caution

- - Install and ground per National Electric Code
  - For single lamp operation, insulate unused blue lead for 600 VRMS.