



**SKU:** 23081-B2

**UPC:**

**Features & Benefits:**

**Description:** Heat Shrinkable End Cap, Conductor Range 4/0-8, Black, Bag of 2

## Specs

### Additional Class Attributes

Container	NA
Model	Cap
Shrink Ratio	3:1

### Dimensions

Cut Length	3.5 in
Expanded ID (IN)	0.75
Expanded ID (mm)	19.05
Height (IN)	0
Height BX (IN)	3.75
Length (IN)	0
Recovered ID (IN)	0.220 IN
Recovered Wall Thickness (IN)	0.080 IN
Weight (LB)	0.1173
Weight BX (LB)	1.568
Width (IN)	0
Width BX (IN)	6.5

### Additional Technical Specifications

Dielectric Strength	500 V/Mil
---------------------	-----------

### Material and Finish

Material	Polyolefin
----------	------------

### General

Bag Quantity	2
Carton Quantity Description	STD PACK QTY 10
NEMA Code	0-000-1
UPC Code	78366971302

### Testing Standards

CSA File Number	NA
Prop65 Compliance	WARNING: Cancer and Reproductive Harm - <a href="http://www.P65warnings.ca.gov">www.P65warnings.ca.gov</a>
UL Control Number	8M24
UL / CULUS Specification	UL 486D Listed
UL File Number	E158587

### Environment and Temperature

Flammability Rating	Not Flammable
Minimum Shrink Temperature	120°C
Operating Temperature	-55°C to 100°C
Temperature Rating	-55°C to 100°C

### Color

Color	Black
-------	-------

### Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	4/0 Str - 8 Str
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	4/0 Str - 8 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA

### Voltage

Voltage Rating	600 V
----------------	-------