



Isostatic Industries, Inc.
 4153 North Kostner Avenue
 Chicago, IL 60641
Toll Free: 800.621.5500
Phone: 773.286.3444
Fax: 773.282.3323
Email: info@isostatic.com

Item # 401074, Oilube® Powdered Metal Bronze SAE841 Sleeve Bearings / Bushings - INCH

Isostatic Oilube® Bearings / Bushings

- Standard stock products
- SAE 841-copper (87-90%), tin (8-9), carbon, other elements
- Powdered metal bronze providing interconnected reservoirs for oil
- Vacuum impregnated with SAE 30 oil during the manufacturing process (approx. 19% by vol.)
- Self-lubricating – when in motion oil rises to the surface for lubrication and restores itself when at rest
- Ideal for heavy loads at moderate speeds or light loads at high speeds – max Pv 50,000, P-Load 2,000, V-SFM-1,200
-

[+ more](#)



[Description](#) | [Specifications](#) | [Dimensions](#) | [Tolerances](#) | [Performance Data](#)

Description

Detailed Description

.377 IN I.D. X .44 IN O.D. X 1 IN Length, SAE 841 Powdered Metal Bronze, Sleeve Bearing

Specifications

Catalog Number	SS-1214-16
Interchange #	SS1214-16
Unit of Measure	Each
Material	Powdered Metal / Oil Impregnated Bronze
Material Standard	SAE 841
Avg Unit Weight	0.0095 lb

UPC Code

00846802043698

Dimensions**Nominal Inner Diameter** 3/8 in**Nominal Outer Diameter** 7/16 in**Nominal Length** 1 in**Tolerances****Inner Diameter Tolerance** +.000 -.001 in**Outside Diameter Tolerance** +.000 -.001 in**Overall Length Tolerance** ± .005 in**Performance Data****Load - P Max Value** 2,000 lb/in²**Speed - V Max Value** 1,200 ft²/min**Load at Speed - PV Max Value (P.S.I. / S.F.M.)** 50,000