



STRAIGHT SHANK



## Slow Spiral Masonry Drills

Part #	Size	X	OAL	Drilling	Shank
502SP4001	1/8"	X	3"	1-1/2"	1/8"
502SP4002	3/16"	X	4"	2-1/2"	3/16"
502SP6001	3/16"	X	6"	4"	3/16"
502SP4732	7/32"	X	4"	2-1/2"	7/32"
502SP4003	1/4"	X	4"	2-1/2"	1/4"
502SP6002	1/4"	X	6"	4"	1/4"
502SP1201	1/4"	X	12"	10"	1/4"
502SP1814	1/4"	X	18"	16"	1/4"
502SP4004	5/16"	X	4"	2-1/2"	1/4"
502SP6003	5/16"	X	6"	4"	1/4"
502SP4005	3/8"	X	4"	2-1/2"	1/4"
502SP6004	3/8"	X	6"	4"	3/8"
502SP1203	3/8"	X	12"	10"	3/8"
502SP1838	3/8"	X	18"	16"	3/8"
502SP6005	7/16"	X	6"	4"	1/4"
502SP4006	1/2"	X	4"	2-1/2"	1/4"
502SP6007	1/2"	X	6"	4"	3/8"
502SP1204	1/2"	X	12"	10"	3/8"
502SP1812	1/2"	X	18"	16"	3/8"
502SP6008	9/16"	X	6"	4"	3/8"
502SP6009	5/8"	X	6"	4"	3/8"
502SP1205	5/8"	X	12"	10"	3/8"
502SP1858	5/8"	X	18"	16"	3/8"
502SP6010	3/4"	X	6"	4"	1/2"
502SP1206	3/4"	X	12"	10"	1/2"
502SP1834	3/4"	X	18"	16"	1/2"
502SP6011	7/8"	X	6"	4"	1/2"
502SP1207	7/8"	X	12"	10"	1/2"
502SP1878	7/8"	X	18"	16"	1/2"
502SP6012	1"	X	6"	4"	1/2"
502SP1208	1"	X	12"	10"	1/2"
502SP1801	1"	X	18"	16"	1/2"

Use with Rotation or Percussion





Cinderblock Brick Concrete Masonry

- ◆ General Purpose
- ◆ Tungsten Carbide
- ◆ Slow Spiral Flute
- ◆ Tempered Body
- ◆ Black Oxide Finish
- ◆ Gold Head
- ◆ Straight Shank
- ◆ ANSI Specification



A first generation carbide tipped drill bit, mass produced since the early 1970's, first in Europe, then in Puerto Rico, then in the USA. Still used ubiquitously and found in anchor kits all over the world.



- ◆ Carbide Tip
- ◆ Bright Finish
- ◆ For Tack Strip



## Carpet Stub Drills

Part #	Size	OAL	Qty.
CD-18	1/8"	1-7/8"	1
CD-18L	1/8"	2-3/4"	1