



**ISOSTATIC**  
LEADERS IN BRONZE BEARINGS...and MORE

**Isostatic Industries, Inc.**  
4153 North Kostner Avenue  
Chicago, IL 60641  
**Toll Free:** 800.621.5500  
**Phone:** 773.286.3444  
**Fax:** 773.282.3323  
**Email:** [info@isostatic.com](mailto:info@isostatic.com)

## Item # 104223, Century® Cast Bronze SAE660 Sleeve Bearings / Bushings - INCH

### Isostatic Century Bronze® Bearings / Bushings

- Standard stock products
- SAE 660 / CA 932-copper 83%, tin 7%, lead 7%, zinc 3%
- Longer length bar up to 105" available on made-to-order basis
- Non-porous, highly dense grain structure for long life
- Offers good hardness, strength and wear resistance; excellent anti-frictional characteristics
- Tensile strength of 35,000 psi, yield strength of 27,000 psi and brinell hardness of 72
- Ideal for heavy loads at moderate speeds or light loads at high speeds –

[+ more](#)



[Description](#) | [Specifications](#) | [Dimensions](#) | [Tolerances](#) | [Performance Data](#)

### Description

#### Detailed Description

3/4 IN I.D. x 15/16 IN O.D. x 2-1/2 IN Length, SAE 660 Cast Bronze, Sleeve Bearing

### Specifications

<b>Catalog Number</b>	CB-1215-20
<b>Interchange #</b>	CB 1215-20 CB121520
<b>Unit of Measure</b>	Each
<b>Material</b>	Cast Bronze
<b>Material Standard</b>	SAE 660

<b>Avg Unit Weight</b>	0.199 lb
------------------------	----------

<b>UPC Code</b>	00846802015329
-----------------	----------------

#### Dimensions

<b>Nominal Inner Diameter</b>	3/4 in
-------------------------------	--------

<b>Nominal Outer Diameter</b>	15/16 in
-------------------------------	----------

<b>Nominal Length</b>	2 1/2 in
-----------------------	----------

#### Tolerances

<b>Inner Diameter Tolerance</b>	±.001 in
---------------------------------	----------

<b>Outside Diameter Tolerance</b>	+.002 to +.003 in
-----------------------------------	-------------------

<b>Overall Length Tolerance</b>	±.005 in
---------------------------------	----------

#### Performance Data

<b>Load - P Max Value</b>	3,000 lb/in <sup>2</sup>
---------------------------	--------------------------

<b>Speed - V Max Value</b>	750 ft <sup>2</sup> /min
----------------------------	--------------------------

<b>Load at Speed - PV Max Value (P.S.I. / S.F.M.)</b>	75,000
---	--------