



ISOSTATIC
LEADERS IN BRONZE BEARINGS...and MORE

Isostatic Industries, Inc.
4153 North Kostner Avenue
Chicago, IL 60641
Toll Free: 800.621.5500
Phone: 773.286.3444
Fax: 773.282.3323
Email: info@isostatic.com

Item # 106515, Century® Cast Bronze SAE660 Solid Bars - INCH

Isostatic Century Bronze® Solid Bars

- Standard stock products – 13" standard length
- SAE 660 / CA 932-copper 83%, tin 7%, lead 7%, zinc 3%
- Longer length bar up to 105" available on made-to-order basis
- Non-porous, highly dense grain structure for long life
- Offers good hardness, strength and wear resistance; excellent anti-frictional characteristics
- Tensile strength of 35,000 psi, yield strength of 27,000 psi and brinell hardness of 72
- Ideal for heavy loads at moderate speeds or light loads at high speeds

[+ more](#)



[Description](#) | [Specifications](#) | [Dimensions](#) | [Tolerances](#) | [Performance Data](#)

Description

Detailed Description

2-1/4 IN O.D. x 13 IN Length, SAE 660 Cast Bronze, Solid Bar

Specifications

| | |
|------------------------|---------------------------------------------------|
| Catalog Number | BS0018-13 |
| Interchange # | B932S000018 B932S000018-13 BS 018 BS0018 |
| Unit of Measure | Each |
| Material | Cast Bronze |

| | |
|--------------------------|----------------|
| Material Standard | SAE 660 |
| Avg Unit Weight | 17.8000 lb |
| UPC Code | 00846802026394 |

Dimensions

| | |
|-------------------------------|----------|
| Nominal Outer Diameter | 2 1/4 in |
| Nominal Length | 13 in |

Tolerances

| | |
|-----------------------------------|-----------------------------------------|
| Outside Diameter Tolerance | Oversized approx .03125" - to finish to |
| Overall Length Tolerance | Oversized approx .03125" - to finish to |

Performance Data

| | |
|-------------------------------------------------------|--------------------------|
| Load - P Max Value | 3,000 lb/in ² |
| Speed - V Max Value | 750 ft ² /min |
| Load at Speed - PV Max Value (P.S.I. / S.F.M.) | 75,000 |