



**ISOSTATIC**  
LEADERS IN BRONZE BEARINGS...and MORE

**Isostatic Industries, Inc.**  
4153 North Kostner Avenue  
Chicago, IL 60641  
**Toll Free:** 800.621.5500  
**Phone:** 773.286.3444  
**Fax:** 773.282.3323  
**Email:** [info@isostatic.com](mailto:info@isostatic.com)

## Item # 401378, Oilube® Powdered Metal Bronze SAE841 Sleeve Bearings / Bushings - INCH

### Isostatic Oilube® Bearings / Bushings

- Standard stock products
- SAE 841-copper (87-90%), tin (8-9), carbon, other elements
- Powdered metal bronze providing interconnected reservoirs for oil
- Vacuum impregnated with SAE 30 oil during the manufacturing process (approx. 19% by vol.)
- Self-lubricating – when in motion oil rises to the surface for lubrication and restores itself when at rest
- Ideal for heavy loads at moderate speeds or light loads at high speeds – max Pv 50,000, P-Load 2,000, V-SFM-1,200
- 

[+ more](#)



[Description](#) | [Specifications](#) | [Dimensions](#) | [Tolerances](#) | [Performance Data](#)

### Description

#### Detailed Description

1.129 IN I.D. X 1.504 IN O.D. X 1-1/4 IN Length, SAE 841 Powdered Metal Bronze, Sleeve Bearing

### Specifications

|                          |   |
|--------------------------|---|
| <b>Catalog Number</b>    | SS-3648-20                              |
| <b>Interchange #</b>     | SS3648-20                               |
| <b>Unit of Measure</b>   | Each                                    |
| <b>Material</b>          | Powdered Metal / Oil Impregnated Bronze |
| <b>Material Standard</b> | SAE 841                                 |

|                        |           |
|------------------------|-----------|
| <b>Avg Unit Weight</b> | 0.2312 lb |
|------------------------|-----------|

|                 |                |
|-----------------|----------------|
| <b>UPC Code</b> | 00846802046736 |
|-----------------|----------------|

#### Dimensions

|                               |          |
|-------------------------------|----------|
| <b>Nominal Inner Diameter</b> | 1 1/8 in |
|-------------------------------|----------|

|                               |          |
|-------------------------------|----------|
| <b>Nominal Outer Diameter</b> | 1 1/2 in |
|-------------------------------|----------|

|                       |          |
|-----------------------|----------|
| <b>Nominal Length</b> | 1 1/4 in |
|-----------------------|----------|

#### Tolerances

|                                 |                  |
|---------------------------------|------------------|
| <b>Inner Diameter Tolerance</b> | + .000 - .001 in |
|---------------------------------|------------------|

|                                   |                   |
|-----------------------------------|-------------------|
| <b>Outside Diameter Tolerance</b> | + .000 - .0015 in |
|-----------------------------------|-------------------|

|                                 |           |
|---------------------------------|-----------|
| <b>Overall Length Tolerance</b> | ± .005 in |
|---------------------------------|-----------|

#### Performance Data

|                           |                          |
|---------------------------|--------------------------|
| <b>Load - P Max Value</b> | 2,000 lb/in <sup>2</sup> |
|---------------------------|--------------------------|

|                            |                            |
|----------------------------|----------------------------|
| <b>Speed - V Max Value</b> | 1,200 ft <sup>2</sup> /min |
|----------------------------|----------------------------|

|   |        |
|---|--------|
| <b>Load at Speed - PV Max Value (P.S.I. / S.F.M.)</b> | 50,000 |
|---|--------|