



™

Kuriyama of America, Inc.

360 E. State Parkway

Schaumburg, IL 60173-5335 USA

Phone: (847) 755-0360**Toll-Free FAX:** (800) 800-0320**International FAX:** (847) 885-0996 **Email:** sales@kuriyama.com**Item # AL-C300, Aluminum Part C Female Coupler x Hose Shank**[Specifications](#) | [Note](#)

Specifications

Size	3 in
Weight Each	2.200 lb
Standard Carton	15
Package Type	Each
Applications	<ul style="list-style-type: none"> • Agriculture • Chemicals/Petroleum • Construction • Fracking • Irrigation • Material Handling
Handles	Forged Brass
Slot Pins	Zinc Plated Carbon Steel

Pull Rings	Zinc Plated Carbon Steel
Gaskets	Buna-N
Safety Clips	Zinc Plated Carbon Steel
Operating Pressure	150 psi
Locking Feature	Safety clips may be inserted to lock handles, preventing disconnection during product transfer.
Type	Female Coupler x Hose Shank
Style	Part C
End Type A	Female Coupler
End Size A	3 in
End Type B	Hose Shank
End Size B	3 in
Material	Aluminum
Features	<ul style="list-style-type: none"> • All sizes except 1/2", 5" and 8" comply with Mil-Spec A-A-59326 for interchangeability • 5" Size complies with ASTM specs for interchangeability • 1/2" x 1/2" are not specified under Mil Specs • All 8" and 10" female couplers supplied with 4 locking handles, safety clips, pull rings and chains • Aluminum alloy is specially designed for high tensile strength, lightness and rigidity • Locking feature using safety clips to prevent disconnection during use on all sizes except 1/2" • Hose shanks specially designed for easy assembly with Tigerflex type hoses • Aluminum couplings supplied with brass handles which results in less wear on connecting parts

Note

-

All sizes except 5" and 8" are made to comply with MIL Spec A-A-

Note

59326 for interchangeability.

Sizes 5" & 8" comply with ASTM Specifications for interchangeability.

1/2" x 1/2" are not specified under MIL Specs.

All 8" couplers supplied with 4 locking handles, safety clips, pull rings and chains at NO CHARGE.