

# McKissick® Bronze Bushed Sheaves

"A" Nominal Outside Diameter (mm)	Stock Number	Pattern Number	Wire Line Size (mm)	"D" Shaft Size (mm)	Hub Width (mm)	Rim Width (mm)	"C" Nominal Hub Outside Diameter (mm)	"B" Nominal Tread Diameter (mm)	Material	Approx. Weight (kg)
124	460478	5-1-B	10	31.8	31.8	28.6	57.0	103	F.S.	1.63
124	2026414	5-1-B	13	31.8	31.8	28.6	57.0	103	F.S.	1.63
124	460469	5-1-B	16	31.8	31.8	28.6	57.0	103	F.S.	1.63
127	907273	1173	5	15.9*	23.8	22.2	57.0	108	P.M.	1.02
127	907291	1173	5	19.1*	23.8	22.2	57.0	108	P.M.	1.02
127	460511	5-1	8	19.1	25.4	22.2	38.1	102	F.S.	1.13
127	907282	1173	10	15.9*	23.8	22.2	57.0	108	P.M.	1.02
127	907308	1173	10	19.1*	23.8	22.2	57.0	108	P.M.	1.02
127	460520	5-1	10	19.1	25.4	22.2	38.1	102	F.S.	1.13
127	460539	5-1	11	19.1	25.4	22.2	38.1	102	F.S.	1.13
127	907326	1173	13	15.9*	27.0	25.4	57.0	102	P.M.	1.13
127	907362	1173	13	15.9*	30.2	28.6	57.0	102	D.I.	1.81
127	907344	1173	13	19.1*	30.2	25.4	57.0	102	P.M.	1.13
127	907380	1173	13	19.1*	30.2	28.6	57.0	102	D.I.	1.81
127	907406	1173	13	22.2*	30.2	28.6	57.0	102	D.I.	1.81
133	460628	6-6	16	25.4	38.1	34.9	52.5	98.5	F.S.	1.81
133	460637	6-6	19	25.4	38.1	34.9	52.5	98.5	F.S.	1.81
149	2023129	6-2	16	38.1	44.5	41.3	63.5	111	F.S.	2.72
149	2023137	6-2	19	38.1	44.5	41.3	63.5	111	F.S.	2.72
149	2023135	6-2	22	38.1	44.5	41.3	63.5	111	F.S.	2.72
152	907424	1173	10	12.7*	20.6	19.1	47.6	127	P.M.	1.13
152	907488	1173	10	12.7*	27.0	25.4	47.6	127	P.M.	1.13
152	907442	1173	10	15.9*	20.6	19.1	47.6	127	P.M.	1.13
152	907503	1173	10	15.9*	27.0	25.4	47.6	127	P.M.	1.13
152	907460	1173	10	19.1*	20.6	19.1	47.6	127	P.M.	1.13
152	907521	1173	10	19.1*	27.0	25.4	47.6	127	P.M.	1.13
152	2026483	6-1	10	19.1*	27.0	25.4	51.0	130	F.S.	1.81
152	916245	6-1	10	22.2*	27.0	25.4	51.0	130	F.S.	1.81
152	2028641	6-1	10	25.4*	27.0	25.4	51.0	130	F.S.	1.81
152	460682	6-1-B	10	31.8	28.4	25.4	57.0	125	F.S.	1.68
152	907549	1173	13	15.9*	30.2	28.6	47.6	124	P.M.	2.27
152	907567	1173	13	19.1*	30.2	28.6	47.6	124	P.M.	2.14
152	913024	1193	13	22.2*	27.0	25.4	47.6	124	P.M.	1.70
152	460879	6-8	13	25.4	38.1	31.8	79.5	121	B.S.	3.18
152	460673	6-1-B	13	31.8*	28.6	25.4	57.0	125	F.S.	1.81
152	2028048	1193	13	25.4*	27.0	25.4	47.6	124	P.M.	4.31
152	2026938	6-1	16	19.1*	27.0	25.4	51.0	130	F.S.	3.18
152	913060	1193	16	19.1*	33.3	31.8	47.6	121	P.M.	1.81
152	916254	6-1	16	22.2*	27.0	25.4	51.0	130	F.S.	1.81
152	913088	1193	16	22.2	33.3	31.8	47.6	121	P.M.	1.70
152	2026822	6-1	16	25.4*	27.0	25.4	51.0	130	F.S.	1.81
152	913104	1193	16	25.4*	33.3	31.8	47.6	121	P.M.	1.70
152	2023264	6NS-2	16	51.0	58.5	55.5	79.5	108	F.S.	4.31
152	460897	6-8	19	25.4	38.1	31.8	79.5	121	B.S.	3.18
152	913168	1193	19	25.4	39.7	38.1	76.0	117	P.M.	3.06
152	2023260	6NS-2	19	51.0	58.5	55.5	79.5	108	F.S.	4.31
152	2023262	6NS-2	22	51.0	58.5	55.5	79.5	108	F.S.	4.31
171	907692	1173	6	19.1*	30.2	28.6	51.0	149	D.I.	2.27
171	907718	1173	6	25.4*	30.2	28.6	51.0	149	D.I.	2.27
171	907709	1173	10	19.1*	30.2	28.6	51.0	149	D.I.	2.27
171	907727	1173	10	25.4*	30.2	28.6	51.0	149	D.I.	2.27
178	461020	7-1	6	38.1	34.9	19.1	60.5	159	B.S.	2.81
178	461039	7-1	10	38.1	34.9	19.1	60.5	159	B.S.	2.81
178	907629	1173	13	19.1*	27.0	25.4	51.0	143	D.I.	1.93
178	907647	1173	13	22.2*	27.0	25.4	51.0	143	D.I.	1.93
191	460986	8-7	16	25.4	38.1	34.9	52.5	160	F.S.	3.40
191	460977	8-7	19	25.4	38.1	34.9	52.5	160	F.S.	3.40
194	461262	8-10	10	25.4	38.1	31.8	60.5	157	D.I.	3.18
194	461280	8-10	13	25.4	38.1	31.8	60.5	157	D.I.	3.18
194	461271	8-10	16	25.4	38.1	31.8	60.5	157	D.I.	3.18

Custom sheaves are available. See page 281 for ordering details.