

## **PIG® Stat-Mat® Absorbent Roll**

MAT418 Lightweight, 30" x 300', 1 roll

The ONLY absorbent mat for fuels and solvents proven to dissipate static.



- The best mat you can buy to reduce the risk of electrostatic discharge; a critical precaution around flammable liquids and vapors
- Stat-Mat Pads and Rolls pass NFPA 99 standards for static decay and surface resistivity, making them perfect for fueling areas and solvent cleanup
- Absorbs and retains oils and fuels - including acetone, benzene, gasoline, toluene, xylene, mineral spirits and jet fuels - but not water
- Lasts 2X longer than ordinary mats for fewer change-outs; Eight layers of 100% polypropylene are thermally bonded to make PIG Mat the strongest mat on the market; won't rip, tear or fray even when saturated
- Exclusive dimple pattern speeds wicking of liquid throughout mat for faster, easier cleanup
- Highly absorbent, fine-fiber construction won't leave behind liquids or fiber residue
- Packaged in special static-dissipative bags to help reduce static charge buildup
- Floats to clean up spills on water
- Flame-resistant material won't burn immediately like cellulose mats; melts when exposed to high heat while on the job
- White color tells you it's only for oils and fuels
- Rolls are ideal for covering large areas and soaking up leaks and overspray
- Easy-tear perforations let you take only what you need, so you use less mat and save money
- Light-weight construction is economical for small tasks and cleanups



### Specifications

<b>Fluid Absorbed</b>	Fuels; Oil-Based Liquids - Not Water
<b>Special Feature</b>	Anti-Static
<b>Color</b>	White
<b>Dimensions</b>	30" W x 300' L
<b>Absorbency</b>	Up to 40.2 gal. per bag

<b>Absorbency per</b>	Up to 40.2 gal. per roll
<b>Durability Level</b>	Normal Foot Traffic
<b>Mat Weight/Absorbency Level</b>	Lightweight
<b>Perforated</b>	Perforated Every 10" Lengthwise
<b>Sold as</b>	1 roll per bag
<b>Weight</b>	30 lbs.
<b># per Pallet</b>	12
<b>Composition</b>	Polypropylene
<b>UNSPSC</b>	47131901
<b>UV Resistant</b>	No
<b>Pigalog® Page Number</b>	<u>Page 53</u>

## Metric Equivalent

<b>Absorbency per</b>	Up to 152.2 L per roll
<b>Absorbency</b>	Up to 152.2 L per bag
<b>Dimensions</b>	76.2cm W x 91m L
<b>Weight</b>	13.6 kg

## Technical Information

### Certifications, Approvals and Ratings

NFPA 99,NFPA 77

### Technical Documents

PIG® Oil-Only Absorbents

29 CFR 1910.106(h)(7(i)(a))

29 CFR 1910.22(a)(2)

40 CFR 112.7

40 CFR 122.26



**One Pork Avenue • Tipton, PA 16684-0304**

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com