

# MAYAN®

DUAL FOCUS LENS AND RATCHETING TEMPLES



## PART

SB2610D\*\*

SB2620D\*\*

## LENS

Clear

Gray

- Lenses block 99.9% of harmful UV rays.
- Crafted of high grade nylon and polycarbonate materials.
- Sleek in-line ratchet adjustable temples provides perfect fit.
- Fashionable, soft rubber straight back temples- no length adjustment necessary.

### GENERAL SPECIFICATION

Bridge: 15.5mm

Closest Point Between Temple Tips: 86mm

Lens Base: 9 Curve

Lens Size Diagonal: 83.5mm

Lens Size Vertical: 48.5mm

Lens Thickness: 2.4mm

Overall Length (Lens-Tip): 160mm

Overall Width (Hinge-Hinge): 139mm

PD: 68mm

Weight: 28gm

**PACKAGING**

Polybag: 1pc



Inner Box: 12 pcs

Case: 300 pcs

**MAYAN**®

DUAL FOCUS LENS AND RATCHETING TEMPLES

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	Height curvature dual focus construction, fit the contours of the face
Frame	Polycarbonate	Streamline, lightweight, fashionable
Side Shields	Polycarbonate	Integral to lens
Nose Bridge	Polycarbonate	V-Bridge, integral to lens
Sleeve Temple	Polycarbonate	Unique ratchet mechanism with style slim design, unique ratchet mechanism allows users to adjust lens angle for a custom fit
Soft Temple Tip	PVC	Brand new soft temple tips give ultimate comfort fit and prevent slippage
Hinge	Polycarbonate	3 barrel type, integral to frame/part (temple)
Screw	Stainless steel	Standard hinge screw

PART	LENS	LENS MARKING	FRAME MARKING
SB2610D	 Clear	P Z87 + U6	P Z87 +
SB2620D	 Gray	P Z87 + U6 L2.5	P Z87 +

**LENS MARKING****Symbols:**

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

H: Small Head Size

S: Special Purpose

**UV Filter Transmittance:**

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%

U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%

U3: Max Effective Far UV= .07% / Max Near UV= 1.4%

U4: Max Effective Far UV= .04% / Max Near UV= .5%

U5: Max Effective Far UV= .02% / Max Near UV= .2%

U6: Max Effective Far UV= .01% / Max Near UV= .1%

**Visible Light Filters:**

L1.3: 85% Max. Visible Light

L1.7: 55% Max. Visible Light

L2.5: 29% Max. Visible Light

L3: 18% Max. Visible Light

**FRAME MARKING****Symbols:**

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact