

# FORUM®

Fashionable Stream Line Design



## Black Frame

Part	Lens
SB6610D •••••	Clear
SB6610DT •••••	Clear H2X Anti-Fog
SB6620D •••••	Gray
SB6670D •••••	Silver Mirror
SB6680D •••••	Indoor/Outdoor Mirror

- Soft PVC nose piece generates a cushion for a comfort fit.
- Metal emblem on temple presents this premium eyewear at the top of its class.
- Fashionable stream line design incorporates the elements of safety in trend setting eyewear.
- 9.5 base curve lens provides excellent side protection, scratch-resistant polycarbonate provides 99.9% UV protection.
- Passes MIL-PRF 32432 High Velocity Impact Standards.

## GENERAL SPECIFICATION

Bridge: 12.4mm
Lens Base: 9.5 Curve
Lens Size Diagonal: 80mm
Lens Size Vertical: 45mm
Lens Thickness: 2.3mm
Overall Length (Lens-Tip): 159mm
Overall Width (Hinge-Hinge): 138mm
PD: 68mm
Weight: 26gm
Closest point between lens: 11.6mm
Closest point between temple tips: 86mm






**PACKAGING**

Polybag: 1pc

Inner Box: 12 pcs

Case: 300 pcs

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	9.5 base wrap around lens
Frame	Polycarbonate	Lens clipped to frame
Nose Piece	PVC	Universal fit
Temple	Polycarbonate	Soft tips for comfort
Hinge	Polycarbonate	3 barrel type
Emblem	Red Bronze	Attached to the temple
Screw	Polycarbonate	Integral to ratchets

PART	LENS	LENS MARKING	FRAME MARKING
SB6610D	 Clear	P Z87 + U6	P Z87 +
SB6610DT	 Clear H2X Anti-Fog	P Z87 + U6	P Z87 +
SB6620D	 Gray	P Z87 + U6 L2.5	P Z87 +
SB6670D	 Silver Mirror	P Z87 + S	P Z87 +
SB6680D	 Indoor/Outdoor Mirror	P Z87 + U6 L1.7	P Z87 +

**LENS MARKING****Symbols:**

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

H: Small Head Size

S: Special Purpose

**UV Filter Transmittance:**

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%

U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%

U3: Max Effective Far UV= .07% / Max Near UV= 1.4%

U4: Max Effective Far UV= .04% / Max Near UV= .5%

U5: Max Effective Far UV= .02% / Max Near UV= .2%

U6: Max Effective Far UV= .01% / Max Near UV= .1%

**Visible Light Filters:**

L1.3: 85% Max. Visible Light

L1.7: 55% Max. Visible Light

L2.5: 29% Max. Visible Light

L3: 18% Max. Visible Light

**FRAME MARKING****Symbols:**

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact