



# Technical Data Sheet

**House & Home Restore Patch-a-Wall  
Product No. 0658**

## Description

A quality, ready mixed vinyl spackling compound formulated to provide long-term durability & excellent adhesion to plaster, drywall, wallboard, wood & primed metal. Formulated to a creamy consistency with excellent paint hold-out & sanding properties.

## Key Features

- Vinyl Latex Based for Easy Water Clean-up
- Easy Application & Tooling
- Excellent Sanding When Fully Cured
- VOC Compliant
- Slightly Off-White for Easy Coverage
- Interior/Exterior
- Contains No Asbestos
- EZ Squeeze Tube

## Uses

Patch-a-Wall provides excellent adhesion to plaster, drywall, wallboard, wood & primed metal. Excellent for filling holes & cracks in interior/exterior walls.

## Surface Preparation

Surface should be clean, dry & free from dust, dirt, grease, oil, mildew, wax & loose paint. Apply when spackling, air & surface temperatures are above 50F (10C) & rising & below 90F. New or unpainted porous surfaces should be primed & allowed to dry before patching.

## Directions

1. Apply with spackling knife & press firmly into crack or small void.
2. Two or more applications may be required for larger cracks & voids. Allow patch to dry for 1-2 hrs between applications, depending upon climatic conditions.
3. When patch is completely dry (1-2 hrs in normal conditions), patch may be sanded smooth.
4. Sanded patch should be dust-free & otherwise clean, prior to priming & painting

<u>Physical/Performance Property</u>	<u>Test Method</u>	<u>Typical Result</u>
Weight Per Gallon	Gardner Cup	10.0 +/- 0.50
Specific Gravity	Calculated	1.20
Total Non Volatile % Solids (Weight)	Computrac Analyzer	77% +/- 2.0
Total Non Volatile % Solids (Volume)	Test Lab	61% +/- 2.0
Viscosity (as packaged)	Brookfield Viscometer	500,000 cps +/- 150,000
Consistency/Appearance	Visual Observation	Creamy, Viscous Paste
pH (initial)	pH Meter	8.5 +/- 0.50
Odor	Subjective	Very Low – Mild Latex
Base Polymer	Known	Vinyl Latex Emulsion Blend
Pigment	Known	Calcium Carbonate
Flash Point	Closed Cup	>200F – Non-Flam/Waterborne
Freeze/Thaw Stability	Test Lab 0 F/77 F @24 hrs or ASTM C731	Pass 5 Cycles
Shelf Life	Lab 50 C Oven – Accelerated	Minimum 1 Yr @ 77F
Slump	Lab Wallboard	None in typical application
Rheological Characteristics	Observation/Test Board Tooling	Thixotropic
Tack Free Time	ASTM D2377	1 hr @ 77F
Storage Conditions	Test Lab	Original Container: 40F to 90F
Application Temperature	Test Lab	50F to 90F
Service Temperature	Lab Oven/QUV/Freezer/OE Fence	0 F to 180 F
Tooling/Workability	Test Lab/Field Evaluation	Excellent @ 50F to 90F
Paintability	Test Lab/Field Evaluation	Excellent @ 1 to 2 hr drying (Latex & Oil-based)

## Clean Up

Clean tools & skin with warm water & soap.

## For Best Results

- Surface should be sound & prepared as described within Surface Preparation
- Apply when product, air & substrate are 50F & rising
- New or unpainted porous surfaces should be primed & allowed to dry before patching
- Sanded patches should be primed & painted
- Deeper cracks & voids should receive multiple applications, allowing patch to dry 1-2 hrs between applications, depending upon temperature, humidity & patch size.

## Color

Slightly off-white

## Packaging

HDPE EZ Squeeze Tube

## Limitations

- Larger holes & cracks may require more than one application; allow patch to dry 1-2 hrs between applications

## Environmental, Safety & Transportation Information

<u>Criteria</u>	<u>Evaluation Method</u>	<u>Status</u>
<i>CARB Compliance</i>	<i>Documents Review</i>	<i>Yes</i>
<i>Prop 65 Ingredients</i>	<i>Documents Review</i>	<i>Yes (See MSDS)</i>
<i>DOT Proper Shipping Name</i>	<i>Review of Regs</i>	<i>Not Regulated by DOT</i>
<i>DOT Hazard</i>	<i>Review of Regs</i>	<i>None</i>
<i>DOT UN/NA Number</i>	<i>Review of Regs</i>	<i>None</i>
<i>Packing Group</i>	<i>Review of Regs</i>	<i>None</i>
<i>VOC Content</i>	<i>Calculated</i>	<i>1.5 to 2%/weight</i>

**CAUTION: NOT FOR INTERNAL CONSUMPTION. KEEP OUT OF REACH OF CHILDREN & PETS. KEEP FROM FREEZING.** Dry or mechanical sanding of this product after use may result in the generation of nuisance dust. When dry sanding the use of a dust/particulate respirator approved by NIOSH should be worn. (See MSDS for additional information).  
**WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.**

## LIMITED WARRANTY

Recommendations for use of this product are based on tests we believe to be reliable. Manufacturer and seller are not responsible for results where this product is used under conditions beyond our control. If when applied as directed, this material fails to perform as represented, it will be replaced without charge upon presentation of proof of purchase and used container. This limited warranty only applies to residential use and damages including consequential damage and other remedies are excluded. No other warranties apply, including fitness for a particular purpose.

TDS Number: 0658TD

Date of Issue: January 25, 2010

SEE MSDS FOR ADDITIONAL DATA/INFORMATION