

Hand Crank / Motor Driven Reels | Series H / 30000

Medium Duty Hand Crank Reels

Series H - Air/Water/Oil/Grease - 3/8", 1/2", 3/4" I.D.

Series H is an economical reel designed for medium duty applications requiring long lengths of hose. It is equally suited for plant or field use such as turf care, pest control, steam cleaning and more. Shipped completely assembled, ready to install.

Made in USA 

Medium duty
H16000



Model without hose	Shipping Weight lbs kg	Hose I.D. in mm	Hose O.D. in mm	Hose Length ft m	Pressure psi bar	(F)NPTF Reel Outlet in	(F)NPTF Reel Inlet in	Size Index #
Low Pressure Air/Water Hose Reels Max temperature 150 °F (65 °C)								
 H16000	32 15	3/8 10	.600 15	300 91	500 35	1/4	3/8	1
H26000	34 15	3/8 10	.600 15	450 137	500 35	1/4	3/8	2
 H18005	33 15	1/2 13	.750 19	175 53	1000 69	1/2	1/2	5
H18000	34 15	1/2 13	.750 19	200 61	1000 69	1/2	1/2	1
H28005	34 15	1/2 13	.750 19	300 91	1000 69	1/2	1/2	4
H28000	37 17	1/2 13	.750 19	300 91	1000 69	1/2	1/2	2
 H19000	33 15	3/4 19	1.075 27	105 32	1000 69	3/4	3/4	1
H29005	36 16	3/4 19	1.075 27	100 30	1000 69	3/4	3/4	3
H29000	41 19	3/4 19	1.075 27	150 46	1000 69	3/4	3/4	2
Medium Pressure Oil Hose Reels Max temperature 210 °F (99 °C)								
 H16000 M	32 15	3/8 10	.710 18	300 91	3000 207	3/8	3/8	1
H18000 M	34 15	1/2 13	.850 22	200 61	3000 207	1/2	1/2	1
H19000 M	38 17	3/4 19	1.188 30	80 24	3000 207	3/4	3/4	1
H29000 M	35 16	3/4 19	1.188 30	150 46	3000 207	3/4	3/4	2
High Pressure Grease Hose Reels Max temperature 210 °F (99 °C)								
H16000 H	35 16	3/8 10	.730 19	250 76	5000 345	3/8	3/8	1

Reels are supplied without hose; assemblies will be quoted upon request. **CAUTION:** To prevent drum damage fully extend and pressurize hose and rewind on the reel. Stainless models available, see page 19.

Dimensions - Size Index										
	1		2		3		4		5	
	in	mm	in	mm	in	mm	in	mm	in	mm
A	19	483	19	483	18 1/8	479	20 1/8	512	20 1/8	512
B	20	508	20	508	14	356	14	356	14	356
C	15	381	15	381	10	254	10	254	10	254
D	10	254	16	407	16	407	16	407	10	254
E	12 1/2	318	18 1/2	470	18 1/2	470	18 1/2	470	12 1/2	318
F	5 3/4	146	5 3/4	146	5 3/4	146	5 3/4	146	5 3/4	146
G	17 3/4	451	17 3/4	451	15 3/16	386	17 3/4	451	17 3/4	451

Drum diameter 8".

Made in USA 

Hand Crank
CA32112 L



Hose Installation: The Series 30000 gooseneck is easily removed from the reel for hose attachment. Simply remove the four fasteners attaching gooseneck to reel, connect hose to the gooseneck and re-connect to the reel. NOTE: Do not discard the O-ring; insure that the O-ring is properly fitted into the grooves when replacing the gooseneck.

Heavy Duty Hand Crank and Motor Driven Reels

Series 30000 - Air/Water/Oil - 1/4", 1/2", 3/4", 1" I.D.

Reelcraft's Series 30000 reels are designed for rugged, heavy duty applications requiring long lengths of hose and large storage capacity. All-bolted unitized construction with no welds to fatigue, full flow swivel and heavy gauge steel frame, spool and drum ensure longest service life. Series 30000's vibration-proof, self-locking fasteners are ideal for industrial or field use such as turf care or pest control.

- ✓ Adjustable spool rotation drag that eliminates hose backlash
- ✓ Motor mounting at either end of reel
- ✓ Nickel-plated swivel with four O-ring options: AFLAS (standard), Buna, Viton® or -EPR* seals *Standard swivel
- ✓ Optional lock pin to prevent spool rotation when the reel is not in use, S600874

Available Options

Pivot Brackets
See page 47



Hose Roller Guides
See page 47



Switches & Motors
See page 48



Replacement Hoses
See page 50



Models listed with an icon can ship same day upon request when the order is received by 11:30 AM Eastern Time for quantities of 5 or fewer.

 Indiana Warehouse

 Indiana & California Warehouses

 California Warehouse

 Canadian Warehouse