

Product data sheet

Characteristics

8910DPA32V02

Contacteur, Definite Purpose, 30A, 2 pole,
5HP at 230VAC, 1 phase, 110/120VAC coil at
50/60Hz, open



Main

Product or Component Type	Definite Purpose Contactor
Line Rated Current	30 A
Number of Poles	2P
Pole contact composition	2 NO
Range of Product	DPA

Complementary

Maximum Horse Power Rating	2 Hp 115 V AC, 1 phase 5 hp 230 V AC, 1 phase
Locked rotor rated current	150 A 460 V AC 120 A 575 V AC 180 A 277 V AC
[Ue] rated operational voltage	600 V AC
[Uc] control circuit voltage	120 V AC 60 Hz 110 V AC 50 Hz
Phase	1 phase
Electrical Connection	Binder head Quick connect terminals
Height	2.31 In (58.67 mm) 2.31 in (58.70 mm)
Width	2.37 In (60.20 mm) 2.4 in (60.2 mm)
Depth	2.90 In (73.66 mm) 3.0 in (76 mm)
Net Weight	0.97 Lb(US) (0.44 kg) 0.98 lb(US) (0.44 kg)

Environment

Product Certifications	UL Recognized[RETURN]CSA
------------------------	--------------------------

Ordering and shipping details

Category	US1CP1B21343
Discount Schedule	CP1B
GTIN	785901116967
Returnability	Yes
Country of origin	CN

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.50 in (6.35 cm)
Package 1 Width	3.100 in (7.874 cm)
Package 1 Length	4.0000000000 in (10.16 cm)
Package 1 Weight	15.680 oz (444.521 g)

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes

Contractual warranty

Warranty	18 months
----------	-----------