

HOM120DF

Mini circuit breaker, Homeline, 20A, 1 pole, 120VAC, 10kA AIR, combo ARC/ground fault, plug in, UL



Main

Product	Miniature circuit-breaker
Range	Homeline
Current Rating	20 A
Certifications	UL Listed
Voltage Rating	120 V AC
Mounting Type	Plug-in
Number of Poles	1P
Short Circuit Current Rating	10 kA
Number of Spaces	1
Circuit Breaker Type	Combination ARC-fault and ground fault class A 6 mA
Ratings	HACR rated
Electrical Connection	Clamp terminal for 2 cables
Wire Size	1 x AWG 14...AWG 8 (aluminium/copper) 2 x AWG 14...AWG 10 (copper)

Complementary

Connections - Terminals	Pigtail neutral
Tightening torque	35.4 lbf.in (4.0 N.m) 0.004...0.009 in ² (2.5...6 mm ²) (AWG 14...AWG 8)
Height	3.13 in (79.50 mm)
Width	1 in (25.4 mm)
Depth	2.98 in (75.69 mm)

Environment

Ambient Air Temperature for Operation	104 °F (40 °C)
---------------------------------------	----------------

Ordering and shipping details

Category	US1DE3D06301
Discount Schedule	DE3D
GTIN	785901741367
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.300 in (3.302 cm)
Package 1 Width	4.0000000000 in (10.16 cm)
Package 1 Length	5.50 in (13.97 cm)
Package 1 Weight	11.200 oz (317.515 g)
Unit Type of Package 2	CAR
Number of Units in Package 2	38
Package 2 Height	3.900 in (9.906 cm)

Package 2 Width	20.700 in (52.578 cm)
Package 2 Length	14.0000000000 in (35.56 cm)
Package 2 Weight	26.050 lb(US) (11.816 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
Halogen content performance	Halogen free product

Contractual warranty

Warranty	Lifetime
----------	----------