

Product data sheet

Characteristics

HOM260

Mini circuit breaker, Homeline, 60A, 2 pole, 120/240VAC, 10kA AIR, standard type, plug in, UL



Main

Product	Miniature circuit-breaker
Range	Homeline
Current Rating	60 A
Certifications	UL Listed
Voltage Rating	120/240 V AC
Mounting Type	Plug-in
Number of Poles	2P
Short Circuit Current Rating	10 kA
Number of Spaces	2
Circuit Breaker Type	Standard
Ratings	HACR rated
Electrical Connection	Box lugs
Wire Size	1 x AWG 8...AWG 2 (aluminium/copper)

Complementary

Tightening torque	40.7 lbf.in (4.6 N.m) (AWG 8...AWG 2)
Height	3.13 in (79.50 mm)
Width	2 in (50.8 mm)
Depth	2.98 in (75.69 mm)

Environment

Ambient Air Temperature for Operation	104 °F (40 °C)
---------------------------------------	----------------

Ordering and shipping details

Category	US1DE3D00046
Discount Schedule	DE3D
GTIN	785901065333
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.78 in (7.05 cm)
Package 1 Width	1.59 in (4.03 cm)
Package 1 Length	3.1 in (8.0 cm)
Package 1 Weight	11.200 oz (317.515 g)
Unit Type of Package 2	BB1
Number of Units in Package 2	5
Package 2 Height	3.100 in (7.874 cm)
Package 2 Width	3.100 in (7.874 cm)
Package 2 Length	10.100 in (25.654 cm)
Package 2 Weight	3.583 lb(US) (1.625 kg)

Unit Type of Package 3	CAR
Number of Units in Package 3	50
Package 3 Height	10.800 in (27.432 cm)
Package 3 Width	7.0000000000 in (17.78 cm)
Package 3 Length	16.400 in (41.656 cm)
Package 3 Weight	36.55 lb(US) (16.58 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	Lifetime
----------	----------