



Main

Product	Single Throw Safety Switch
Duty Rating	Light duty
Device Application	Furnace Garages
Disconnect Type	Fusible disconnect
Factory Installed Neutral	Neutral (factory installed)
Phase	3 phase
Number of Poles	2
Current Rating	30 A
Voltage Rating	240 V AC
NEMA degree of protection	NEMA 1
Motor power hp	0.5 Hp at 120 V AC 50-60 Hz for 1 phase motors 2 Hp at 120 V AC 50-60 Hz for 1 phase motors 1.5 Hp at 240 V AC 50-60 Hz for 1 phase motors 3 hp at 240 V AC 50-60 Hz for 1 phase motors

Complementary

Short-circuit current	10 kA
Fuse Type	H or J
Mounting Type	Surface
Wire Size	AWG 14...AWG 8 copper AWG 12...AWG 8 aluminium
Tightening torque	30 Lbf.In (3.39 N.m) 0.00...0.01 in ² (2.082...8.367 mm ²) (AWG 14...AWG 8) 30 lbf.in (3.39 N.m) 0.01...0.01 in ² (3.307...8.367 mm ²) (AWG 12...AWG 8)
Depth	4 in (101.6 mm)
Width	6.13 in (155.70 mm)
Height	7.63 in (193.80 mm)

Environment

Product Certifications	UL listed file E2875
------------------------	----------------------

Ordering and shipping details

Category	US1DE1A00057
Discount Schedule	DE1A
GTIN	785901499022
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.50 in (11.43 cm)
Package 1 Width	6.800 in (17.272 cm)
Package 1 Length	8.900 in (22.606 cm)
Package 1 Weight	3.360 lb(US) (1.524 kg)
Unit Type of Package 2	PAL

Number of Units in Package 2	200
Package 2 Height	40.0000000000 in (101.6 cm)
Package 2 Width	40.0000000000 in (101.6 cm)
Package 2 Length	48.0000000000 in (121.92 cm)
Package 2 Weight	698.00 lb(US) (316.607 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months
----------	-----------