



## Main

Product or Component Type	Miniature circuit-breaker
Range of Product	QOU
Circuit breaker type	Standard
Circuit breaker application	HACR rated

## Complementary

Line Rated Current	60 A
Electrical connection	Slotted box lugs, line side Slotted box lugs, load side
[Ue] rated operational voltage	120/240 V AC 120 V AC 48 V DC
Mounting Mode	Unit mount
AWG gauge	AWG 14...AWG 2 aluminium/copper
Height	4.05 in (102.87 mm)
Width	1.5 in (38.1 mm)
Depth	2.95 in (74.93 mm)
Tightening torque	45 lbf.in (5.08 N.m) (AWG 14...AWG 2)

## Environment

Product Certifications	UL Listed[RETURN]CSA[RETURN]IEC
------------------------	---------------------------------

## Ordering and shipping details

Category	US10DE200900
Discount Schedule	0DE2
GTIN	785901418801
Returnability	Yes
Country of origin	MX

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.600 in (9.144 cm)
Package 1 Width	4.800 in (12.192 cm)
Package 1 Length	2.100 in (5.334 cm)
Package 1 Weight	12.800 oz (362.874 g)
Unit Type of Package 2	CAR
Number of Units in Package 2	24
Package 2 Height	3.700 in (9.398 cm)

Package 2 Width	13.600 in (34.544 cm)
Package 2 Length	20.800 in (52.832 cm)
Package 2 Weight	19.4 lb(US) (8.8 kg)
Unit Type of Package 3	PAL
Number of Units in Package 3	288
Package 3 Height	40.0000000000 in (101.6 cm)
Package 3 Width	42.0000000000 in (106.68 cm)
Package 3 Length	48.0000000000 in (121.92 cm)
Package 3 Weight	272.000 lb(US) (123.377 kg)

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 <a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant with Exemptions
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
RoHS exemption information	 <a href="#">Yes</a>
Circularity Profile	No need of specific recycling operations
Halogen content performance	Halogen free product

### Contractual warranty

Warranty	18 months
----------	-----------