



Actual

Catalog Number: XC730-5
Product ID: 7TAA135100R0000
UPC Number: 78599118313
Status: Active

Cable Lok Set Screw Connector, Size Range 0.450 Inch - 0.610 Inch or 1/2 Inch Knockout, AC Steel 14/2 14/3 14/4 12/2 12/3 12/4 10/2, AC Aluminum Interlocked 14/2 14/3 14/4 12/2 12/3 12/4 10/2, MC (I) Steel 14/2 14/2 14/4 12/2 12/3 12/4 10/2 10/3, MC (I) Aluminum 14/2 14/3 14/4 12/2 12/3 12/4, Flex RW 3/8 Steel and Aluminum 10/2 10/3, Material Zinc Plated Steel with Nylon Insulator, Bag of 5

North American Specifications (UNSPSC)

UNSPSC	39121419 Flex connectors
IGCC	4580 Set-Screw Connectors
Brand Name	Steel City
Type	Cable Lok Connectors
Material	Steel
Finish	Zinc-Chromatic
Temperature Rating	221 Degrees F/105 Degrees C

European Specifications (ETIM)

ETIM	EC001180 Screw connection for protective metallic hose
Nominal size in inch	1/2 inch
Model	Straight
Revolving thread	N
Construction type	No thread
One-piece	Y
Material housing	Zinc die-cast
Surface protection	Untreated
Approved in combination with protective conduit DIN EN 61386-23	N
Approved in combination with protective conduit FI	N

Packaging

Inner Quantity	25
Inner Dimensions (inches)	11.4x6.5x5
Outer Quantity	100
Outer Dimensions (inches)	13.5x12x11
Weight Uom	45.38 lbs. per 100

For further technical assistance, please contact us...

Thomas & Betts - USA
 860 Ridge Lake Blvd.
 Memphis, TN 38120
 www.tnb.com

T&B Technical Support
 MS 3B-50
 860 Ridge Lake Blvd.
 Memphis, TN 38120

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email:techsupport@tnb.com